

PRODUCT DATA SHEET

Kalifa II Suspension 1200 Direct Emission - T16 1x54W - White

**DESIGN BY :**

Ernesto Gismondi

MATERIALS :

Extruded Aluminium

DESCRIPTION :

Single pendant light with direct lighting using 28W and 54W T16 fluorescent light source. Extruded aluminium body with a white or grey paint finish, available in lengths of 1188mm and 2400mm.


Super pure aluminium optics. Light output ratio: 82%. DARK LIGHT emission is in compliance with EN12464-1 standard. Electronic control gear, with or without dimming control. Emergency lighting on request. Quick adjustment steel suspension cables.

Light emission

Dual Emission

IP20  **TECHNICAL DATA SHEET****Features**

| | |
|----------------|---|
| Product name: | Kalifa II Suspension 1200 Direct Emission - T16 1x54W - White |
| Article Code: | M166920 |
| Colour: | White |
| Material: | Extruded Aluminium |
| Series: | Architectural |
| Environment: | Indoor |
| Area contract: | |

Dimensions**OPTICS**

| | |
|-----------|---------------|
| Emission: | Dual Emission |
|-----------|---------------|

DIMENSIONS

| | |
|-----------------|----------|
| Length: | (cm) 118 |
| Width: | (cm) 8 |
| Height: | (cm) 9.3 |
| Cutout shape: | |
| Weight: | 5.1 |
| Glow Wire Test: | 960 ° |

LAMPS NOT INCLUDED

| | |
|-------------------------|--------|
| Category: | FLUO |
| Number: | 1 |
| Lbs: | T16 |
| Watt: | 54 |
| Socket: | G5 |
| Type: | FDH-54 |
| Luminous Flux (lm): | 4450 |
| Colour Rendering: | 85 |
| Colour temperature (K): | 3000 |
| Duration (h): | 20000 |

LAMPIP20  **ELECTRICAL**

| | |
|----------|-----------------------|
| Starter: | Electronic Integrated |
| Voltage: | 220V-240V |