

PRODUCT DATA SHEET

Kalifa II Suspension 1200 Direct Emission - T16 1x54W dimmable - White



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Extruded Aluminium


DESCRIPTION :

Single pendant light with direct lighting using 28W and 54W T16 fluorescent light source. Extruded aluminium body with a white or grey paint finish, available in lengths of 1188mm and 2400mm.

Super pure aluminium optics. Light output ratio: 82%. DARK LIGHT emission is in compliance with EN12464-1 standard. Electronic control gear, with or without dimming control. Emergency lighting on request. Quick adjustment steel suspension cables.

Light emission

Dual Emission




TECHNICAL DATA SHEET

Features

Product name:	Kalifa II Suspension 1200 Direct Emission - T16 1x54W dimmable - White
Article Code:	M166921
Colour:	White
Material:	Extruded Aluminium
Series:	Architectural
Environment:	Indoor
Area contract:	

Dimensions



OPTICS

Emission:	Dual Emission
-----------	---------------

DIMENSIONS

Length:	(cm) 118
Width:	(cm) 8
Height:	(cm) 9.3
Cutout shape:	
Weight:	5.1
Glow Wire Test:	960 °

LAMPS NOT INCLUDED

Category:	FLUO
Number:	1
Lbs:	T16
Watt:	54
Socket:	G5
Type:	FDH-54
Luminous Flux (lm):	4450
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

LAMP



ELECTRICAL

Starter:	Electronic dimmable DALI Integrated
Voltage:	220V-240V