

PRODUCT DATA SHEET

Kalifa II Suspension 2400 Direct Emission - T16 2x28-54W dimmable - Grey

**DESIGN BY :**

Ernesto Gismondi

MATERIALS :

Extruded Aluminium


DESCRIPTION :

Single pendant light with direct lighting using 28W and 54W T16 fluorescent light source. Extruded aluminium body with a white or grey paint finish, available in lengths of 1188mm and 2400mm.

Super pure aluminium optics. Light output ratio: 82%. DARK LIGHT emission is in compliance with EN12464-1 standard. Electronic control gear, with or without dimming control. Emergency lighting on request. Quick adjustment steel suspension cables.

Light emission


Dual Emission



TECHNICAL DATA SHEET

Features

Product name:	Kalifa II Suspension 2400 Direct Emission - T16 2x28-54W dimmable - Grey
Article Code:	M167091
Colour:	Grey
Material:	Extruded Aluminium
Series:	Architectural
Environment:	Indoor
Area contract:	

Dimensions**OPTICS**

Emission:	Dual Emission
-----------	---------------

DIMENSIONS

Length:	(cm) 240
Width:	(cm) 8
Height:	(cm) 9.3
Cutout shape:	
Weight:	8.9
Glow Wire Test:	960 °

LAMPS NOT INCLUDED

Category:	FLUO
Number:	2
Lbs:	T16
Watt:	54
Socket:	G5
Type:	FDH-54
Luminous Flux (lm):	4450
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

LAMP**ELECTRICAL**

Starter:	Electronic dimmable DALI Integrated
Voltage:	220V-240V