

PRODUCT DATA SHEET

Kalifa II Suspension 1640 Dual Emission - T16 2x24W - Grey

**DESIGN BY :**

Ernesto Gismondi

MATERIALS :

Extruded Aluminium

DESCRIPTION :

Single pendant light with direct-indirect lighting using 2x24W and 2x54W T16 fluorescent light source. Extruded aluminium body with a white or grey paint finish, available in lengths of 1640mm and 2900mm. Super pure aluminium optics. Light output ratio: 92%. Light distribution: 30% indirect and 70% direct. DARK LIGHT emission is in compliance with EN12464-1 standard. Electronic control gear, with or without dimming control. Quick adjustment steel suspension cables.

Light emission


Dual Emission

IP20  

TECHNICAL DATA SHEET

Features

Product name:	Kalifa II Suspension 1640 Dual Emission - T16 2x24W - Grey
Article Code:	M167190
Colour:	Grey
Material:	Extruded Aluminium
Series:	Architectural
Environment:	Indoor
Area contract:	

Dimensions**OPTICS**



Emission:	Dual Emission
-----------	---------------

DIMENSIONS

Length:	(cm) 164
Width:	(cm) 8
Height:	(cm) 5
Cutout shape:	
Weight:	4.8
Glow Wire Test:	960 °

LAMPS NOT INCLUDED

Category:	FLUO
Number:	2
Lbs:	T16
Watt:	24
Socket:	G5
Type:	FDH-24
Luminous Flux (lm):	1750
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

LAMPIP20  **ELECTRICAL**

Starter:	Electronic Integrated
Voltage:	220V-240V