

PRODUCT DATA SHEET

Kalifa II Suspension 2900 Dual Emission - T16 2x28-54W dimmable - Grey



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Extruded Aluminium

DESCRIPTION :

Single pendant light with direct-indirect lighting using 2x24W and 2x54W T16 fluorescent light source. Extruded aluminium body with a white or grey paint finish, available in lengths of 1640mm and 2900mm. Super pure aluminium optics. Light output ratio: 92%. Light distribution: 30% indirect and 70% direct. DARK LIGHT emission is in compliance with EN12464-1 standard. Electronic control gear, with or without dimming control. Quick adjustment steel suspension cables.

Light emission

Dual Emission




TECHNICAL DATA SHEET

Features

| | |
|----------------|--|
| Product name: | Kalifa II Suspension 2900 Dual Emission - T16 2x28-54W dimmable - Grey |
| Article Code: | M167291 |
| Colour: | Grey |
| Material: | Extruded Aluminium |
| Series: | Architectural |
| Environment: | Indoor |
| Area contract: | |

Dimensions



OPTICS

| | |
|-----------|---------------|
| Emission: | Dual Emission |
|-----------|---------------|

DIMENSIONS

| | |
|-----------------|----------|
| Length: | (cm) 290 |
| Width: | (cm) 8 |
| Height: | (cm) 5 |
| Cutout shape: | |
| Weight: | 8.4 |
| Glow Wire Test: | 960 ° |

LAMPS NOT INCLUDED

| | |
|-------------------------|--------|
| Category: | FLUO |
| Number: | 2 |
| Lbs: | T16 |
| Watt: | 54 |
| Socket: | G5 |
| Type: | FDH-54 |
| Luminous Flux (lm): | 4450 |
| Colour Rendering: | 85 |
| Colour temperature (K): | 3000 |
| Duration (h): | 20000 |

LAMP



ELECTRICAL

| | |
|----------|-------------------------------------|
| Starter: | Electronic dimmable DALI Integrated |
| Voltage: | 220V-240V |