# PRODUCT DATA SHEET

## Kalifa II Ceiling 1200 - T16 28W dimmable - White



### **DESIGN BY :**

Ernesto Gismondi

## MATERIALS :

Extruded Aluminium

## **DESCRIPTION**:

Ceiling light using 28W and 54W T16 fluorescent light source. Extruded aluminium body with a white or grey paint finish, available in lengths of 1188mm and 2400mm. Super pure aluminium optics. Light output ratio: 82%. DARK LIGHT emission is in compliance with EN12464-1 standard. Electronic control gear, with or without dimming control. Emergency lighting on request. Ceiling light using 28W and 54W T16 fluorescent light source. Extruded aluminium body with a white or grey paint finish, available in lengths of 1188mm and 2400mm. Super pure aluminium optics. Light output ratio: 82%. DARK LIGHT emission is in compliance with EN12464-1 standard. Electronic control gear, with or without dimming control. Emergency lighting on request. Ceiling light using 28W and 54W T16 fluorescent light source. Extruded aluminium body with a white or grey paint finish, available in lengths of 1188mm and 2400mm. Super pure aluminium optics. Light output ratio: 82%. DARK LIGHT emission is in compliance with EN12464-1 standard. Electronic control gear, with or without dimming control. Emergency lighting on request.

#### Light emission

Direct Dark Light





## **TECHNICAL DATA SHEET**

## Features

Product name: Article Code: Colour: Material: Series:

Environment:

Area contract:

DIMENSIONS

Cutout shape: Weight:

Glow Wire Test:

OPTICS Emission:

Length:

Width:

Height:

Kalifa II Ceiling 1200 - T16 28W dimmable - White M181321 White Extruded Aluminium Architectural Indoor

Direct Dark Light

(cm) 118

(cm) 8

5.1

960 °

(cm) 9.3

## Dimensions

1188

LAMP IP20 ↔ 🕅



## ELECTRICAL

Starter: Voltage: Electronic dimmable DALI Integrated 220V-240V

| Category:               | FLUO   |
|-------------------------|--------|
| Number:                 | 1      |
| Lbs:                    | T16    |
| Watt:                   | 28     |
| Socket:                 | G5     |
| Туре:                   | FDH-28 |
| Luminous Flux (Im):     | 2600   |
| Colour Rendering:       | 80-85  |
| Colour temperature (K): | 3000   |
| Class:                  | A      |

LAMPS NOT INCLUDED