PRODUCT DATA SHEET

Kalifa II Ceiling 1200 - T16 54W dimmable - Grey



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Extruded Aluminium

DESCRIPTION:

Ceiling light using 28W and 54W T16 fluorescent light source. Extruded aluminium body with a white or grey paint finish, available in lengths of 1188mm and 2400mm. Super pure aluminium optics. Light output ratio: 82%. DARK LIGHT emission is in compliance with EN12464-1 standard. Electronic control gear, with or without dimming control. Emergency lighting on request. Ceiling light using 28W and 54W T16 fluorescent light source. Extruded aluminium body with a white or grey paint finish, available in lengths of 1188mm and 2400mm. Super pure aluminium optics. Light output ratio: 82%. DARK LIGHT emission is in compliance with EN12464-1 standard. Electronic control gear, with or without dimming control. Emergency lighting on request. Ceiling light using 28W and 54W T16 fluorescent light source. Extruded aluminium body with a white or grey paint finish, available in lengths of 1188mm and 2400mm. Super pure aluminium optics. Light output ratio: 82%. DARK LIGHT emission is in compliance with EN12464-1 standard. Electronic control gear, with or without dimming control. Emergency lighting on request.

Light emission

Direct Dark Light





TECHNICAL DATA SHEET

Features

Material:

Series:

OPTICS Emission:

Length:

Width:

Height:

Product name: Article Code: Colour:

Environment:

Area contract:

DIMENSIONS

Cutout shape: Weight:

Glow Wire Test:

Kalifa II Ceiling 1200 - T16 54W dimmable - Grey M181591 Grey Extruded Aluminium Architectural Indoor

Direct Dark Light

(cm) 118

(cm) 8

5.1

960 °

(cm) 9.3

Dimensions

1188 D

LAMP

IP20 🛈 🕅



ELECTRICAL

Starter: Voltage: Electronic dimmable DALI Integrated 220V-240V

Category:	FLUO
Number:	1
Lbs:	T16
Watt:	54
Socket:	G5
Туре:	FDH-54
Luminous Flux (Im):	4450
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

LAMPS NOT INCLUDED