

PRODUCT DATA SHEET

Kalifa System - T16 2x35W - Grey

**DESIGN BY :**

Ernesto Gismondi

MATERIALS :

Extruded Aluminium

DESCRIPTION :

Modular pendant system with direct-indirect lighting using T16 fluorescent light source. Continuous linear mounting or with 90° connectors. Extruded aluminium body with a 4mm thick silkscreen printed glass. Light output ratio: 56%. Light distribution: 39% indirect and 61% direct. Electronic control gear, with or without dimming control, and emergency lighting. Polycarbonate dust-protection screen. Quick adjustment steel suspension cables. End caps, connectors and suspension wires are to be ordered separately. Complies with standard EN60598-1 and other specific standards.

Light emission

Indirect Flood/direct Dark Light

IP20

TECHNICAL DATA SHEET**Features**

Product name:	Kalifa System - T16 2x35W - Grey
Article Code:	M165690
Colour:	Grey
Material:	Extruded Aluminium
Series:	Architectural
Environment:	Indoor
Area contract:	

Dimensions**OPTICS**

Emission: Indirect Flood/direct Dark Light

DIMENSIONS

Length:	(cm) 153
Width:	(cm) 20
Height:	(cm) 5
Cutout shape:	
Weight:	8.2
Glow Wire Test:	850 °

LAMPS NOT INCLUDED

Category:	FLUO
Number:	2
Lbs:	T16
Watt:	35
Socket:	G5
Type:	FDH-35
Luminous Flux (lm):	3300
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

LAMP

IP20

ELECTRICAL

Starter:	Electronic Integrated
Voltage:	220V-240V

ACCESSORIES



KALIFA SYSTEM - End cap
(1 piece). 200x50x3mm.
grey M166390



KALIFA SYSTEM - 90°
connector (unwired).
224x224x50mm. 1,30kg.
grey M166490



KALIFA SYSTEM -
Suspension cable. Ceiling
plate Ø100mm. 1400mm.
grey M166190



KALIFA SYSTEM - Steel
suspension wire with
power feed cable. Ceiling
plate Ø100mm. 1400mm.
3 wires (3x1,5mm²). Grey
M166290



KALIFA SYSTEM - Steel
suspension wire with
power feed cable. Ceiling
plate Ø100mm. 1400mm.
5 wires (3x1,5mm² + 2x0,
5mm²). grey M166090