

PRODUCT DATA SHEET

Kalifa System - T16 2x54W + emergency - Grey

DESIGN BY:

Ernesto Gismondi

MATERIALS:

Extruded Aluminium

DESCRIPTION:

Modular pendant system with direct-indirect lighting using T16 fluorescent light source. Continuous linear mounting or with 90° connectors. Extruded aluminium body with a 4mm thick silkscreen printed glass. Light output ratio: 56%. Light distribution: 39% indirect and 61% direct. Electronic control gear, with or without dimming control, and emergency lighting. Polycarbonate dust-protection screen. Quick adjustment steel suspension cables. End caps, connectors and suspension wires are to be ordered separately. Complies with standard EN60598-1 and other specific standards.

Light emission

Indirect Flood/direct Dark Light





Features Product name:

Kalifa System - T16 2x54W +

emergency - Grey

Article Code: M165597
Colour: Grey

Material: Extruded Aluminium
Series: Architectural

Environment: Indoor

Area contract:

OPTICS

Emission: Indirect Flood/direct Dark Light

DIMENSIONS

 Length:
 (cm) 123

 Width:
 (cm) 20

 Height:
 (cm) 5

Cutout shape:

Weight: 7.5 Glow Wire Test: 850 °

LAMPS NOT INCLUDED

Category: FLUO Number: Lbs: T16 Watt: 54 G5 Socket: FDH-54 Type: Luminous Flux (Im): 4450 Colour Rendering: 85 Colour temperature (K): 3000 20000 Duration (h):

Dimensions



LAMP



ELECTRICAL

Starter: Electronic Integrated

Emergency availability: Integrated Emergency duration: 1 hour Voltage: 220V-240V

Artemide

ACCESSORIES



KALIFA SYSTEM - End cap (1 piece). 200x50x3mm. grey M166390



KALIFA SYSTEM - 90° connector (unwired). 224x224x50mm. 1,30kg. grey M166490



KALIFA SYSTEM -Suspension cable. Ceiling plate Ø100mm. 1400mm. grey M166190



KALIFA SYSTEM - Steel suspension wire with power feed cable. Ceiling plate Ø100mm. 1400mm. 3 wires (3x1,5mm²). Grey M166290



KALIFA SYSTEM - Steel suspension wire with power feed cable. Ceiling plate Ø100mm. 1400mm. 5 wires (3x1,5mm² + 2x0,5mm²). grey M166090