

PRODUCT DATA SHEET

Kalifa System - T16 2x54W dimmable - White



DESIGN BY :

Ernesto Gismondi

MATERIALS :


Extruded Aluminium

DESCRIPTION :

Modular pendant system with direct-indirect lighting using T16 fluorescent light source. Continuous linear mounting or with 90° connectors. Extruded aluminium body with a 4mm thick silkscreen printed glass. Light output ratio: 56%. Light distribution: 39% indirect and 61% direct. Electronic control gear, with or without dimming control, and emergency lighting. Polycarbonate dust-protection screen. Quick adjustment steel suspension cables. End caps, connectors and suspension wires are to be ordered separately. Complies with standard EN60598-1 and other specific standards.

Light emission

Indirect Flood/direct Dark Light




TECHNICAL DATA SHEET

Features

Product name:	Kalifa System - T16 2x54W dimmable - White
Article Code:	M165521
Colour:	White
Material:	Extruded Aluminium
Series:	Architectural
Environment:	Indoor
Area contract:	

Dimensions



OPTICS

Emission: Indirect Flood/direct Dark Light

DIMENSIONS

Length:	(cm) 123
Width:	(cm) 20
Height:	(cm) 5
Cutout shape:	
Weight:	6.6
Glow Wire Test:	850 °

LAMPS NOT INCLUDED

Category:	FLUO
Number:	2
Lbs:	T16
Watt:	54
Socket:	G5
Type:	FDH-54
Luminous Flux (lm):	4450
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

LAMP



ELECTRICAL

Starter:	Electronic dimmable DALI Integrated
Voltage:	220V-240V

ACCESSORIES



KALIFA SYSTEM - End cap (1 piece). 200x50x3mm. white M166320



KALIFA SYSTEM - 90° connector (unwired). 224x224x50mm. 1,30kg. white M166420



KALIFA SYSTEM - Suspension cable. Ceiling plate Ø100mm. 1400mm. white M166120



KALIFA SYSTEM - Steel suspension wire with power feed cable. Ceiling plate Ø100mm. 1400mm. 3 wires (3x1,5mm²). white M166220



KALIFA SYSTEM - Steel suspension wire with power feed cable. Ceiling plate Ø100mm. 1400mm. 5 wires (3x1,5mm² + 2x0,5mm²). white M166020



INTERACTIVE-DALI remote control. M104900