

PRODUCT DATA SHEET

Luceri Led Soft - 37W 4000K Dim. DALI

**DESIGN BY :**

Artemide

MATERIALS :

Polycarbonate

DESCRIPTION :

Recessed fixed round luminaires with high-efficiency LED-module with frame. Recessing ring in polycarbonate. Reflector made from technopolymers with smooth specular metallised coating with an anti-scratch protective layer. The optics system consists of a lighting chamber with integral passive thermal management system, and featured with CREE TRUE WHITE® technology, an intelligent system that guarantees a constant colour temperature and permanent colour rendering index throughout entire service life. High luminous flux: 2000 lm (27W) and 2900 lm (37W) available with warm white (3000K) and neutral white (4000K) tones. Symmetric wide-beam light distribution. CRI > 90. Reflector with glare-control: URG < 19 conforming to EN12464-1 standard. Service life: 50000 hours at 70% luminous flux. Spring system for a tool-free recessed mounting in ceilings with thickness ranging from 1 to 25 mm. Luminaire comes complete with LED-module and DALI dimmable electronic driver. Bridging connection is possible. Dust-protection screen in transparent polycarbonate as an optional extra, installed by simple twist-and-lock mechanism. Complies with standard EN60598-1 and other specific standards.

CRI > 90

Light emission

Downlighting

IP20



TECHNICAL DATA SHEET

Features

Product name:	Luceri Led Soft - 37W 4000K Dim. DALI
Article Code:	M239100
Colour:	N/s
Material:	Polycarbonate
Series:	Architectural
Environment:	Indoor
Area contract:	Hospitality Hotel, Hospitality Restaurant, Office

OPTICS


Emission: Downlighting

DIMENSIONS

Height:	(cm) 20.9
Cutout width:	(cm) 29.1
Cutout diameter:	(cm) 29.2
Recessed depth:	(cm) 25
Cutout shape:	Rounded
Weight:	1.5
Glow Wire Test:	750 °

LAMPS INCLUDED

Category:	LED
Watt:	37
Luminous Flux (lm):	2900
Number:	1 x 1
Typology:	1
Color Rendering:	>90
Color temperature (K):	4000
Class:	A

Dimensions**LAMP**

IP20

**ELECTRICAL**

Starter:	Electronic dimmable DALI Included
Voltage:	230/240V



LUCERI LED transparent
polycarbonate screen
M239200