

PRODUCT DATA SHEET

Andromeda Suspension 300x300 Direct Emission - T16-R 1x22W + QR111 1xmax50W



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Extruded Aluminium

DESCRIPTION :

A range of multisource luminaires combining diffused lighting via T16 and T16-R fluorescent lamps and accent lighting via 1, 2, 3 or 4 adjustable spotlights using 12V halogen and metal-halide lamps. 3 options available: recessed, ceiling, or pendant with direct lighting. Extruded aluminium body with grey paint finish. Polycarbonate diffuser. Die-cast aluminium spotlights in steel boxes with a black paint finish. Each spot can be directed individually: tilt angle ranging from -10° to +70°, rotation of up to 355°. Integral electronic control gear. Integral electronic transformer for the halogen accent lighting, dimmable by trailing edge external dimmers. 2 separate switch circuits for the independent control of the diffused and accent lighting functions. Complies with standard EN60598-1 and other specific standards.

Dimmable by trailing edge external dimmer.
Maximum suspension 1300

Light emission

Direct Diffused And Accent Lighting




TECHNICAL DATA SHEET

Features

Product name:	Andromeda Suspension 300x300 Direct Emission - T16-R 1x22W + QR111 1xmax50W
Article Code:	M116420
Colour:	Grey
Material:	Extruded Aluminium
Series:	Architectural
Environment:	Indoor
Area contract:	

Dimensions



OPTICS

Emission: Direct Diffused And Accent Lighting

DIMENSIONS

Length:	(cm) 31.2
Width:	(cm) 31.2
Height:	(cm) 14.5
Inclination:	-10/+70
Rotation:	355
Cutout shape:	
Weight:	5.4
Glow Wire Test:	850 °

LAMPS NOT INCLUDED

Category:	HALO
Number:	1
Lbs:	QR111
Watt:	50
Socket:	G53
Type:	HMGS/UB
Colour Rendering:	100
Colour temperature (K):	3000

Category:	FLUO
Number:	1
Lbs:	T16-r
Watt:	22
Socket:	2gx13
Type:	Fsch
Colour Rendering:	1b
Colour temperature (K):	3000

LAMP



ELECTRICAL

Starter:	Electronic
Transformer availability:	Integrated
Voltage:	220V-240V

