


PRODUCT DATA SHEET

Nulla 610 - LED amber



DESIGN BY :

Format Design Studio

MATERIALS :

Aluminium,painted Steel

DESCRIPTION :

Recessed unit with indirect lighting with T16 fluorescent light source, and pathlighting with colored LEDs. Body consisting of a low-depth recessing casing (only 50mm deep) to be sealed in the wall, and a motorized opening shutter. Recessing casing made of steel and fitted with an extruded aluminum frame that requires a finish coat of plaster. 2 size options depending on the light source: 210x610mm (24W T16), and 210x1210mm (54W T16). When the fluorescent lamp is turned on, the shutter is automatically in open position, the indirect lighting is then in service. The turning off of the fluorescent bulb and the closing of the shutter are simultaneous. The LEDs, powered by a separate switch circuit, illuminate the inside of the casing regardless of the position of the shutter. If it is closed, the peripheral illumination of the light fixture provides a pathlighting function. If the shutter is open, the colored light provides a decorative effect. Electronic control gear. Includes led lamps and 230-240V driver unit. Optional recessing box for installation in concrete walls. Not suitable for ceiling mounting. Complies with standard EN60598-1 and other specific standards.

Coloured LED (amber) included. Fluorescent T16 lamp to be ordered separately.

Light emission

Indirect

IP20  

TECHNICAL DATA SHEET

Features

Product name:	Nulla 610 - LED amber
Article Code:	M184020
Colour:	White
Material:	Aluminium,painted Steel
Series:	Architectural
Environment:	Indoor
Area contract:	

OPTICS

Emission:	Indirect
-----------	----------

DIMENSIONS

Length:	(cm) 61
Width:	(cm) 5
Height:	(cm) 21
Cutout Width:	(cm) 63.6
Recessed depth:	(cm) 23.6
Weight:	4.9
Glow Wire Test:	960 °


LAMPS INCLUDED

Category:	LED
Watt:	3
Typology:	Led
Color Rendering:	N/s

LAMPS NOT INCLUDED

Category:	FLUO
Number:	1
Lbs:	T16
Watt:	24
Socket:	G5
Type:	FDH-24
Luminous Flux (lm):	1750
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

Dimensions



LAMP

IP20  

ELECTRICAL

Starter:	Electronic Integrated
Voltage:	220V-240V

ACCESSORIES



NULLA 600 - Recessing
box for concrete walls.
298x684mm M184800