

# PRODUCT DATA SHEET

## Nota Bene Suspension 1200 - T16 1x28W - White



### **DESIGN BY:**

Artemide

### **MATERIALS:**

Painted Steel

### **DESCRIPTION:**

Pendant system with direct-indirect lighting using 28W and 54W T16 fluorescent lamps. Available as a single pendant light or as a modular system. Steel body with a white or grey paint finish, available in lengths of 1234mm and 24116mm.Dark light optic made from super pure aluminium. Dark light emission is in compliance with EN12464-1 st with average luminance levels lower than the 1000 cd/m² limit for an observation angle of 65° or above with respect to the vertical axis . Light output ratio: 91% (1xT16), and 87% (2xT16).Light distribution: 65% indirect and 35% direct (1xT16), 63% indirect and 37% direct (2xT16).Electronic ballast or Dali-Switchdim dimmable electronic ballast.The system comprises of power supply units with ceiling plate and power supply cable, and continuity modules. Intermodule mechanical connection by linear or 90° connectors. Electrical connection via quick connectors. Quick adjustment steel suspension cables. Complies with standard EN60598-1 and other specific standards.

#### Light emission



Indirect/Direct



IP20 Û ∰ ▼

## **TECHNICAL DATA SHEET**

# **Features**

Nota Bene Suspension 1200 - T16 1x28W - White Product name:

Article Code: M106620 White Colour: Material: Painted Steel Series: Architectural

Environment: Area contract:

### **OPTICS**

Emission: Indirect/Direct

## **DIMENSIONS**

Length: (cm) 123 Width: (cm) 16 Height: (cm) 4.8


Cutout shape:

Weight: Glow Wire Test: 850°

## LAMPS NOT INCLUDED

Category: FLUO Number: Lbs: T16 Watt: 28 G5 Socket: FDH-28 Type: Luminous Flux (Im): 2600 Colour Rendering: 85 Colour temperature (K): 3000 Duration (h): 20000

## Dimensions



## LAMP



### **ELECTRICAL**

Starter: Electronic Integrated Voltage: 220V-240V