

# PRODUCT DATA SHEET

# Java 180 Rectangular - 4 lamps QR111



#### **DESIGN BY:**

Ernesto Gismondi

#### **MATERIALS:**

Steel

#### **DESCRIPTION:**

Series of rectangular and square recessed luminaires. Single or multiple light sources. Materials: Adjustable sphere in black steel, frame in metal grey painted with scratch-proof opaque embossed finish. Asymmetrical reflector in aluminium for wall washer version. Versions: 1 lamp - square frame. 2 lamps - rectangular frame. 3 lamps - rectangular frame. 4 lamps - square or rectangular frame. Wall washer - square frame. Sources: 12V dichroic halogen lamps QR-CB 51. Halogen QR 111. Metal halide HSR 111. Linear fluorescent T 16. Accessories: Safety glass. A range of recessed downlights using QR-LP111/12V halogen and HIR-CE111 metal-halide lamps. Square and rectangular models with 2, 3 or 4 lamps. Steel body with frame in grey paint finish. Can be recessed in false ceilings of 1mm to 35mm thick. Each spotlight may be adjusted with a tilt angle ranging from -20° to +70° and rotation of up to 355°. Lamps can be maintained without the need for tools. Remote control gear.

#### Light emission



# **TECHNICAL DATA SHEET**

#### **Features**

Product name: Java 180 Rectangular - 4 lamps

QR111

Article Code: M049565
Colour: Grey
Material: Steel
Series: Architectural


#### **DIMENSIONS**

Length: (cm) 55.5 (cm) 18 Width: (cm) 16.5 Height: Cutout length: (cm) 15.8 **Cutout Width:** (cm) 53.3 Recessed depth: (cm) 16.5 Inclination: -20+70 Rotation: 350 3.2 Weight: Glow Wire Test: 960 9

#### LAMPS NOT INCLUDED

HALO Category: Number: OR111 Lbs: Watt: 100 Socket: HMGS/UB Type: Colour Rendering: 100 Colour temperature (K): 3000 Duration (h): 3000

### **Dimensions**





#### LAMP



## **ELECTRICAL**

**Trasformer availability:** Remote **Voltage:** 12V

# Artemide

# **ACCESSORIES**



Electronic transformer 230-240V/12V. Class II. Dimmable by trailing or leading edge external dimmers. 35-105W. 102x51x30mm. M070412



Electronic transformer 230-240V/12V. Class II. Dimmable by trailing or leading edge external dimmers. 35-150W. 189x38x34mm. M072111



Electronic transformer 230-240V/12V. Class II. Dimmable by trailing or leading edge external dimmers. 10-60W. 123x32x23mm. M070211