

## PRODUCT DATA SHEET

### Java 180 Rectangular - 4 lamps HIR111



**DESIGN BY :**  
Ernesto Gismondi

**MATERIALS :**  
Steel

**DESCRIPTION :**  
Series of rectangular and square recessed luminaires. Single or multiple light sources. Materials: Adjustable sphere in black steel, frame in metal grey painted with scratch-proof opaque embossed finish. Asymmetrical reflector in aluminium for wall washer version. Versions: 1 lamp - square frame. 2 lamps - rectangular frame. 3 lamps - rectangular frame. 4 lamps - square or rectangular frame. Wall washer - square frame. Sources: 12V dichroic halogen lamps QR-CB 51. Halogen QR 111. Metal halide HSR 111. Linear fluorescent T 16. Accessories: Safety glass. A range of recessed downlights using QR-LP111/12V halogen and HIR-CE111 metal-halide lamps. Square and rectangular models with 2, 3 or 4 lamps. Steel body with frame in grey paint finish. Can be recessed in false ceilings of 1mm to 35mm thick. Each spotlight may be adjusted with a tilt angle ranging from -20° to +70° and rotation of up to 355°. Lamps can be maintained without the need for tools. Remote control gear.

#### Light emission



### TECHNICAL DATA SHEET

#### Features

Product name:	Java 180 Rectangular - 4 lamps HIR111
Article Code:	M049555
Colour:	Grey
Material:	Steel
Series:	Architectural


#### DIMENSIONS

Length:	(cm) 55.5
Width:	(cm) 18
Height:	(cm) 16.5
Cutout length:	(cm) 15.8
Cutout Width:	(cm) 53.3
Recessed depth:	(cm) 16.5
Inclination:	-20+70
Rotation:	350
Weight:	3.2
Glow Wire Test:	960 °

#### LAMPS NOT INCLUDED

Category:	HQI
Number:	4
Lbs:	HIR111
Watt:	70
Socket:	GX8.5
Type:	MRS/UB-70
Colour Rendering:	80-85
Colour temperature (K):	3000

#### Dimensions



#### LAMP



#### ELECTRICAL

Starter:	Electronic Remote
Voltage:	220V-240V

## ACCESSORIES

---



Electronic ballast 230-240V. Class I. For HIT 1x70W. 150x80x35mm. M070522



Electronic ballast 230-240V. Class I. For HIT 2x35W. 180x80x34mm. M070422



Electronic ballast 230-240V. Class I. For HIT 1x35W. 155x83x32mm. M070322