

# PRODUCT DATA SHEET

# Java 180 Square - 4 lamps HIR111



#### **DESIGN BY:**

Ernesto Gismondi

#### **MATERIALS:**

Steel

## **DESCRIPTION:**

Series of rectangular and square recessed luminaires. Single or multiple light sources. Materials: Adjustable sphere in black steel, frame in metal grey painted with scratch-proof opaque embossed finish. Asymmetrical reflector in aluminium for wall washer version. Versions: 1 lamp - square frame. 2 lamps - rectangular frame. 3 lamps - rectangular frame. 4 lamps - square or rectangular frame. Wall washer - square frame. Sources: 12V dichroic halogen lamps QR-CB 51. Halogen QR 111. Metal halide HSR 111. Linear fluorescent T 16. Accessories: Safety glass. A range of recessed downlights using QR-LP111/12V halogen and HIR-CE111 metal-halide lamps. Square and rectangular models with 2, 3 or 4 lamps. Steel body with frame in grey paint finish. Can be recessed in false ceilings of 1mm to 35mm thick. Each spotlight may be adjusted with a tilt angle ranging from -20° to +70° and rotation of up to 355°. Lamps can be maintained without the need for tools. Remote control gear.

## Light emission



# **TECHNICAL DATA SHEET**

Features

Java 180 Square - 4 lamps HIR111

Product name: Java 180
Article Code: M049655
Colour: Grey
Material: Steel

Series: Architectural

## **DIMENSIONS**

Length: (cm) 30.5 (cm) 30.5 Width: (cm) 16.5 Height: Cutout length: (cm) 28.3 Cutout Width: (cm) 28.3 Recessed depth: (cm) 16.5 Inclination: -20+70 350 Rotation: Cutout shape: Squared Weight: 2.9 Glow Wire Test: 960°

## LAMPS NOT INCLUDED

 Category:
 HQI

 Number:
 4

 Lbs:
 HIR111

 Watt:
 70


 Socket:
 GX8.5

 Type:
 MRS/UB-70

 Colour Rendering:
 80-85

 Colour temperature (K):
 3000

#### Dimensions



### LAMP



# **ELECTRICAL**

Starter: Electronic Remote
Voltage: 220V-240V

# Artemide

## **ACCESSORIES**



Electronic ballast 230-240V. Class I. For HIT 1x70W. 150x80x35mm. M070522



Electronic ballast 230-240V. Class I. For HIT 2x35W. 180x80x34mm. M070422



Electronic ballast 230-240V. Class I. For HIT 1x35W. 155x83x32mm. M070322