PRODUCT DATA SHEET

Picto 125 LED Ceiling - 4000K - Black/White



DESIGN BY :

Artemide

MATERIALS : Aluminium

DESCRIPTION:

Directional spotlight using monochromatic Led with neutral white tone. Comes with surface plate for ceiling mounting. Body made from aluminium and injection moulded high-quality polyamide. Tilt angle ranging from -90° to 90°, rotation of up to 355°. Precise inclination by means of a graduation specially designed, with a locking mechanism. Electronic power supply. Wide range of accessories. Not suitable for wall installation. Complies with standard EN60598-1 and other specific standards.

Optic MFL (2x10° < angle < 2x15°)

Light emission



IP20 🛈 🕅

TECHNICAL DATA SHEET

Features

Colour:

Material:

OPTICS Emission:

Series:


Product name: Article Code:

Environment:

Area contract:

Picto 125 LED Ceiling - 4000K -Black/White M225811MFL Black/White Aluminium Architectural Indoor Retail, Museum & Exihibitions, , Private Residence

Dimensions



0 0

DIMENSIONS

Width:	(cm) 12.7
Height:	(cm) 17.2
Cutout width:	(cm) 12.7
Inclination:	-90/+90
Rotation:	355
Cutout shape:	
Weight:	2.3
Glow Wire Test:	850 °

LAMPS INCLUDED

Category:	LED
Watt:	33
Wattage (Single):	33
Luminous Flux (Im):	1174
Number:	1 x 1
Typology:	1
Color temperature (K):	4000
Class:	A

Accent Lighting

- - - -

LAMP

IP20 🚸 🕅

ELECTRICAL

Trasformer availability: Voltage: Integrated 220V-240V

Artemide

ACCESSORIES



PICTO 125 - Accessoryholder + Chromatic filter 'Warmtone". White M083617











PICTO 125 - Accessoryholder + Louvre (black). white M083317



PICTO 125 - Accessoryholder + wall washer screen (black). white M083117



PICTO 125 - Accessoryholder + Adjustable dowser (black). white M082917