

PRODUCT DATA SHEET

Andromeda Recessed 300x300 - T16-R 1x22W + QR-CBC 1xmax50W



DESIGN BY:

Ernesto Gismondi

MATERIALS:

Extruded Aluminium

DESCRIPTION:

A range of multisource luminaires combining diffused lighting via T16 and T16-R fluorescent lamps and accent lighting via 1, 2, 3 or 4 adjustable spotlights using 12V halogen and metal-halide lamps. 3 options available: recessed, ceiling, or pendant with direct lighting. Extruded aluminium body with grey paint finish. Polycarbonate diffuser. Die-cast aluminium spotlights in steel boxes with a black paint finish. Each spot can be directed individually: tilt angle ranging from -10° to +70°, rotation of up to 355°. The recessed version can be installed into plasterboard false ceilings, using the recessing frame provided, and into false ceilings systems with 600x600mm and 625x625mm modules. Integral electronic control gear. Integral electronic transformer for the halogen accent lighting, dimmable by trailing edge external dimmers. 2 separate switch circuits for the independent control of the diffused and accent lighting functions. Complies with standard EN60598-1 and other specific standards.

Dimmable by trailing edge external dimmer.

Light emission

Direct Diffused And Accent Lighting



TECHNICAL DATA SHEET

Product name: Andromeda Recessed 300x300 -

T16-R 1x22W + QR-CBC 1xmax50W

Article Code: M115040

Colour: N/s

Material: Extruded Aluminium
Series: Architectural
Environment: Indoor

Area contract:

OPTICS

Features

Emission: Direct Diffused And Accent Lighting

DIMENSIONS

Length: (cm) 29 (cm) 29 Width: Cutout length: (cm) 29.2 **Cutout Width:** (cm) 29.2 Recessed depth: (cm) 13.7 Inclination: -10/+70 Rotation: 355 Cutout shape: Squared Weight: 3.5 Glow Wire Test: 850°

LAMPS NOT INCLUDED

 Category:
 FLUO

 Number:
 1

 Lbs:
 T16-r

 Watt:
 22

 Socket:
 2gx13

 Type:
 Fsch

 Colour Rendering:
 1b

 Colour temperature (K):
 3000

 Category:
 HALO

 Number:
 1

 Lbs:
 QR-CBC51

 Watt:
 50

 Socket:
 GU5.3

 Type:
 HRGS/UB

 Colour Rendering:
 100

Dimensions



LAMP



ELECTRICAL

Starter: Electronic Trasformer availability: Integrated Voltage: 220V-240V



Colour temperature (K):

3000