

PRODUCT DATA SHEET

Andromeda Recessed 300x600 - T16 2x24W + QR-CBC 2xmax50W



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Alluminio Estruso

DESCRIPTION :

A range of multisource luminaires combining diffused lighting via T16 and T16-R fluorescent lamps and accent lighting via 1, 2, 3 or 4 adjustable spotlights using 12V halogen and metal-halide lamps. 3 options available: recessed, ceiling, or pendant with direct lighting. Extruded aluminium body with grey paint finish. Polycarbonate diffuser. Die-cast aluminium spotlights in steel boxes with a black paint finish. Each spot can be directed individually: tilt angle ranging from -10° to +70°, rotation of up to 35°. The recessed version can be installed into plasterboard false ceilings, using the recessing frame provided, and into false ceilings systems with 600x600mm and 625x625mm modules. Integral electronic control gear. Integral electronic transformer for the halogen accent lighting, dimmable by trailing edge external dimmers. 2 separate switch circuits for the independent control of the diffused and accent lighting functions. Complies with standard EN60598-1 and other specific standards.

Dimmable by trailing edge external dimmer.

Light emission

Direct Diffused And Accent Lighting




TECHNICAL DATA SHEET

Features

| | |
|----------------|--|
| Product name: | Andromeda Recessed 300x600 - T16 2x24W + QR-CBC 2xmax50W |
| Article Code: | M115240 |
| Material: | Alluminio Estruso |
| Series: | Architectural |
| Environment: | Indoor |
| Area contract: | |

Dimensions



OPTICS

Emission: Direct Diffused And Accent Lighting

DIMENSIONS

| | |
|-----------------|-----------|
| Length: | (cm) 59 |
| Width: | (cm) 29 |
| Cutout length: | (cm) 29.2 |
| Cutout Width: | (cm) 59.2 |
| Recessed depth: | (cm) 13.7 |
| Inclination: | -10/+70 |
| Rotation: | 355 |
| Weight: | 5.8 |
| Glow Wire Test: | 850 ° |

LAMPS NOT INCLUDED

| | |
|-------------------------|--------|
| Category: | FLUO |
| Number: | 2 |
| Lbs: | T16 |
| Watt: | 24 |
| Socket: | G5 |
| Type: | FDH-24 |
| Luminous Flux (lm): | 1750 |
| Colour Rendering: | 85 |
| Colour temperature (K): | 3000 |
| Duration (h): | 20000 |

| | |
|-------------------|----------|
| Category: | HALO |
| Number: | 2 |
| Lbs: | QR-CBC51 |
| Watt: | 50 |
| Socket: | GU5.3 |
| Type: | HRGS/UB |
| Colour Rendering: | 100 |

LAMP



ELECTRICAL

| | |
|---------------------------|------------|
| Starter: | Electronic |
| Transformer availability: | Integrated |
| Voltage: | 220V-240V |

