

## PRODUCT DATA SHEET

### Andromeda Recessed 300x900 - T16 2x21W + QR-CBC 3xmax50W



#### DESIGN BY :

Ernesto Gismondi

#### MATERIALS :

Alluminio Estruso

#### DESCRIPTION :

A range of multisource luminaires combining diffused lighting via T16 and T16-R fluorescent lamps and accent lighting via 1, 2, 3 or 4 adjustable spotlights using 12V halogen and metal-halide lamps. 3 options available: recessed, ceiling, or pendant with direct lighting. Extruded aluminium body with grey paint finish. Polycarbonate diffuser. Die-cast aluminium spotlights in steel boxes with a black paint finish. Each spot can be directed individually: tilt angle ranging from  $-10^{\circ}$  to  $+70^{\circ}$ , rotation of up to  $355^{\circ}$ . The recessed version can be installed into plasterboard false ceilings, using the recessing frame provided, and into false ceilings systems with 600x600mm and 625x625mm modules. Integral electronic control gear. Integral electronic transformer for the halogen accent lighting, dimmable by trailing edge external dimmers. 2 separate switch circuits for the independent control of the diffused and accent lighting functions. Complies with standard EN60598-1 and other specific standards.

Dimmable by trailing edge external dimmer.

#### Light emission

Direct Diffused And Accent Lighting



### TECHNICAL DATA SHEET

#### Features

Product name:	Andromeda Recessed 300x900 - T16 2x21W + QR-CBC 3xmax50W
Article Code:	M115340
Material:	Alluminio Estruso
Series:	Architectural
Environment:	Indoor
Area contract:	

#### Dimensions



#### OPTICS

Emission:	Direct Diffused And Accent Lighting
-----------	-------------------------------------

#### DIMENSIONS

Length:	(cm) 89
Width:	(cm) 29
Cutout length:	(cm) 29.2
Cutout Width:	(cm) 89.2
Recessed depth:	(cm) 13.7
Inclination:	$-10/+70$
Rotation:	355
Weight:	8.2
Glow Wire Test:	850 °

#### LAMPS NOT INCLUDED

Category:	HALO
Number:	3
Lbs:	QR-CBC51
Watt:	50
Socket:	GU5.3
Type:	HRGS/UB
Colour Rendering:	100
Colour temperature (K):	3000

Category:	FLUO
Number:	2
Lbs:	T16
Watt:	21
Socket:	G5
Type:	FDH-21
Luminous Flux (lm):	1900
Colour Rendering:	85
Colour temperature (K):	3000

#### LAMP



#### ELECTRICAL

Starter:	Electronic
Transformer availability:	Integrated
Voltage:	220V-240V

