Artemide

PRODUCT DATA SHEET

Andromeda Recessed 300x900 - T16 2x21W + HIR111 3xmax35W



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Alluminio Estruso

DESCRIPTION:

A range of multisource luminaires combining diffused lighting via T16 and T16-R fluorescent lamps and accent lighting via 1, 2, 3 or 4 adjustable spotlights using 12V halogen and metal-halide lamps. 3 options available: recessed, ceiling, or pendant with direct lighting. Extruded aluminium body with grey paint finish. Polycarbonate diffuser. Die-cast aluminium spotlights in steel boxes with a black paint finish. Each spot can be directed individually: tilt angle ranging from -10° to +70°, rotation of up to 355°. The recessed version can be installed into plasterboard false ceilings, using the recessing frame provided, and into false ceilings systems with 600x600mm and 625x625mm modules. Integral electronic control gear. Integral electronic transformer for the halogen accent lighting, dimmable by trailing edge external dimmers. 2 separate switch circuits for the independent control of the diffused and accent lighting functions. Complies with standard EN60598-1 and other specific standards.

Light emission

Direct Diffused And Accent Lighting



TECHNICAL DATA SHEET

Features

- Product name:
- Article Code: Material: Series: Environment: Area contract:

OPTICS Emission: Andromeda Recessed 300x900 -T16 2x21W + HIR111 3xmax35W M115350 Alluminio Estruso Architectural Indoor

Dimensions



Direct Diffused And Accent Lighting

DIMENSIONS

Length: (cm) 89 Width: (cm) 29 Cutout length: (cm) 29.2 Cutout Width: (cm) 89.2 Recessed depth: (cm) 13.7 Inclination: -10/+70 Rotation: 355 Weight: 8.2 Glow Wire Test: 850 °

LAMPS NOT INCLUDED

Category:	HQI
Number:	3
Lbs:	HIR111
Watt:	35
Socket:	GX8.5
Туре:	MRS/UB-35
Colour Rendering:	80-85
Colour temperature (K):	3000
Category:	FLUO
Category: Number:	FLUO 2
0 ,	
Number:	2
Number: Lbs:	2 T16
Number: Lbs: Watt:	2 T16 21
Number: Lbs: Watt: Socket:	2 T16 21 G5
Number: Lbs: Watt: Socket: Type:	2 T16 21 G5 FDH-21
Number: Lbs: Watt: Socket: Type: Luminous Flux (Im):	2 T16 21 G5 FDH-21 1900

LAMP

IP20 🛈 🌆 🕅

ELECTRICAL

Starter: Voltage: Electronic Integrated 220V-240V

Dimensions