

PRODUCT DATA SHEET

Andromeda Recessed 300x1200 - T16 2x28W + QR-CBC 4xmax50W

**DESIGN BY :**

Ernesto Gismondi

MATERIALS :

Alluminio Estruso

DESCRIPTION :

A range of multisource luminaires combining diffused lighting via T16 and T16-R fluorescent lamps and accent lighting via 1, 2, 3 or 4 adjustable spotlights using 12V halogen and metal-halide lamps. 3 options available: recessed, ceiling, or pendant with direct lighting. Extruded aluminium body with grey paint finish. Polycarbonate diffuser. Die-cast aluminium spotlights in steel boxes with a black paint finish. Each spot can be directed individually: tilt angle ranging from -10° to +70°, rotation of up to 35°. The recessed version can be installed into plasterboard false ceilings, using the recessing frame provided, and into false ceilings systems with 600x600mm and 625x625mm modules. Integral electronic control gear. Integral electronic transformer for the halogen accent lighting, dimmable by trailing edge external dimmers. 2 separate switch circuits for the independent control of the diffused and accent lighting functions. Complies with standard EN60598-1 and other specific standards.

Dimmable by trailing edge external dimmer.

Light emission


Direct Diffused And Accent Lighting



TECHNICAL DATA SHEET

Features

Product name:	Andromeda Recessed 300x1200 - T16 2x28W + QR-CBC 4xmax50W
Article Code:	M115440
Material:	Alluminio Estruso
Series:	Architectural
Environment:	Indoor
Area contract:	

Dimensions**OPTICS**

Emission: Direct Diffused And Accent Lighting

DIMENSIONS

Length:	(cm) 119
Width:	(cm) 29
Cutout length:	(cm) 29.2
Cutout Width:	(cm) 119
Recessed depth:	(cm) 13.7
Inclination:	-10/+70
Rotation:	355
Weight:	9.2
Glow Wire Test:	850 °

LAMPS NOT INCLUDED

Category:	FLUO
Number:	2
Lbs:	T16
Watt:	28
Socket:	G5
Type:	FDH-28
Luminous Flux (lm):	2600
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

Category:	HALO
Number:	4
Lbs:	QR-CBC51
Watt:	50
Socket:	GU5.3
Type:	HRGS/UB
Colour Rendering:	100

LAMP**ELECTRICAL**

Starter:	Electronic
Transformer availability:	Integrated
Voltage:	220V-240V

