

PRODUCT DATA SHEET

Andromeda Recessed 600x600 - T16 3x24W + QR111 4xmax50W



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Alluminio Estruso

DESCRIPTION :

A range of multisource luminaires combining diffused lighting via T16 and T16-R fluorescent lamps and accent lighting via 1, 2, 3 or 4 adjustable spotlights using 12V halogen and metal-halide lamps. 3 options available: recessed, ceiling, or pendant with direct lighting. Extruded aluminium body with grey paint finish. Polycarbonate diffuser. Die-cast aluminium spotlights in steel boxes with a black paint finish. Each spot can be directed individually: tilt angle ranging from -10° to +70°, rotation of up to 355°. The recessed version can be installed into plasterboard false ceilings, using the recessing frame provided, and into false ceilings systems with 600x600mm and 625x625mm modules. Integral electronic control gear. Integral electronic transformer for the halogen accent lighting, dimmable by trailing edge external dimmers. 2 separate switch circuits for the independent control of the diffused and accent lighting functions. Complies with standard EN60598-1 and other specific standards.

Dimmable by trailing edge external dimmer.

Light emission

Direct Diffused And Accent Lighting

IP20    

TECHNICAL DATA SHEET

Features

| | |
|----------------|---|
| Product name: | Andromeda Recessed 600x600 - T16 3x24W + QR111 4xmax50W |
| Article Code: | M115620 |
| Colour: | N/s |
| Material: | Alluminio Estruso |
| Series: | Architectural |
| Environment: | Indoor |
| Area contract: | |

OPTICS

| | |
|-----------|-------------------------------------|
| Emission: | Direct Diffused And Accent Lighting |
|-----------|-------------------------------------|

DIMENSIONS


| | |
|-----------------|-----------|
| Length: | (cm) 59 |
| Width: | (cm) 59 |
| Cutout length: | (cm) 59.2 |
| Cutout Width: | (cm) 59.2 |
| Recessed depth: | (cm) 13.7 |
| Inclination: | -10/+70 |
| Rotation: | 355 |
| Cutout shape: | Squared |
| Weight: | 10 |
| Glow Wire Test: | 850 ° |

LAMPS NOT INCLUDED

| | |
|-------------------------|--------|
| Category: | FLUO |
| Number: | 3 |
| Lbs: | T16 |
| Watt: | 24 |
| Socket: | G5 |
| Type: | FDH-24 |
| Luminous Flux (lm): | 1750 |
| Colour Rendering: | 85 |
| Colour temperature (K): | 3000 |
| Duration (h): | 20000 |

| | |
|-----------|-------|
| Category: | HALO |
| Number: | 4 |
| Lbs: | QR111 |
| Watt: | 50 |
| Socket: | G53 |

Dimensions



LAMP

IP20    

ELECTRICAL

| | |
|---------------------------|------------|
| Starter: | Electronic |
| Transformer availability: | Integrated |
| Voltage: | 220V-240V |

Artemide

Type: HMGS/UB
Colour Rendering: 100
Colour temperature (K): 3000