

## PRODUCT DATA SHEET

### Andromeda Recessed 600x600 for False Ceiling 625x625 - T16 3x24W + HIR111 4xmax35W



#### DESIGN BY :

Ernesto Gismondi

#### MATERIALS :

Alluminio Estruso

#### DESCRIPTION :

A range of multisource luminaires combining diffused lighting via T16 and T16-R fluorescent lamps and accent lighting via 1, 2, 3 or 4 adjustable spotlights using 12V halogen and metal-halide lamps. 3 options available: recessed, ceiling, or pendant with direct lighting. Extruded aluminium body with grey paint finish. Polycarbonate diffuser. Die-cast aluminium spotlights in steel boxes with a black paint finish. Each spot can be directed individually: tilt angle ranging from -10° to +70°, rotation of up to 355°. The recessed version can be installed into plasterboard false ceilings, using the recessing frame provided, and into false ceilings systems with 600x600mm and 625x625mm modules. Integral electronic control gear. Integral electronic transformer for the halogen accent lighting, dimmable by trailing edge external dimmers. 2 separate switch circuits for the independent control of the diffused and accent lighting functions. Complies with standard EN60598-1 and other specific standards.

Dimmable by trailing edge external dimmer.  
Only for 24mm tee ceiling.

#### Light emission

Direct Diffused And Accent Lighting



## TECHNICAL DATA SHEET

#### Features

Product name:	Andromeda Recessed 600x600 for False Ceiling 625x625 - T16 3x24W + HIR111 4xmax35W
Article Code:	M114952
Colour:	N/s
Material:	Alluminio Estruso
Series:	Architectural
Environment:	Indoor
Area contract:	

#### OPTICS

Emission: Direct Diffused And Accent Lighting

#### DIMENSIONS


Length:	(cm) 59.9
Width:	(cm) 59.9
Cutout length:	(cm) 62.5
Cutout Width:	(cm) 62.5
Recessed depth:	(cm) 13.7
Inclination:	-10/+70
Rotation:	355
Cutout shape:	Squared
Weight:	9.9
Glow Wire Test:	850 °

#### LAMPS NOT INCLUDED

Category:	HQI
Number:	4
Lbs:	HIR111
Watt:	35
Socket:	GX8.5
Type:	MRS/UB-35
Colour Rendering:	80-85
Colour temperature (K):	3000

Category:	FLUO
Number:	3
Lbs:	T16
Watt:	24
Socket:	G5

#### Dimensions



#### LAMP



#### ELECTRICAL

Starter:	Electronic Integrated
Voltage:	220V-240V

# Artemide

---

Type:	FDH-24
Luminous Flux (lm):	1750
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000