

PRODUCT DATA SHEET

Andromeda Ceiling 300x300 - T16-R 1x22W + QR-CBC 1xmax50W



DESIGN BY:

Ernesto Gismondi

MATERIALS:

Extruded Aluminium

DESCRIPTION:

A range of multisource luminaires combining diffused lighting via T16 and T16-R fluorescent lamps and accent lighting Arange of midiscource durinates combining unities of injituding via 1, 2, 3 or 4 adjustable spotlights using 12V halogen and metal-halide lamps. 3 option available: recessed, ceiling, or pendant with direct lighting. Extruded aluminium body with grey paint finish. Polycarbonate diffuser. Die-cast aluminium spotlights in steel boxes with a black paint finish. Each spot can be directed individually: tilt angle ranging from -10° to +70°, rotation of up to 355°. Integral electronic control gear. Integral electronic transformer for the halogen accent lighting, dimmable by trailing edge external dimmers. 2 separate switch circuits for the independent control of the diffused and accent I ighting functions. Complies with standard EN60598-1 and other specific

Dimmable by trailing edge external dimmer.

Light emission

Direct Diffused And Accent Lighting



TECHNICAL DATA SHEET

Andromeda Ceiling 300x300 - T16-R 1x22W + QR-CBC 1xmax50W Product name:

Article Code: M115740

Colour: Grey

Material: Extruded Aluminium Series: Architectural

Environment:

Area contract:

Features

OPTICS

Emission: Direct Diffused And Accent Lighting

DIMENSIONS

Length: (cm) 31.2 Width: (cm) 31.2 Height: (cm) 14.5 Inclination: -10/+70 Rotation: 355

Cutout shape:

Weight: Glow Wire Test: 850°

LAMPS NOT INCLUDED

FLUO Category: Number: T16-r Lbs: Watt: 22 Socket: 2gx13 Fsch Colour Rendering: Colour temperature (K): 3000

Category: HALO Number:

Lbs: QR-CBC51 Watt: 50 GU5.3 Socket: HRGS/UB Type: Colour Rendering: 100 Colour temperature (K): 3000

Dimensions



LAMP



ELECTRICAL

Starter: Electronic Trasformer availability: Integrated Voltage: 220V-240V