

PRODUCT DATA SHEET

Andromeda Ceiling 300x600 - T16 2x24W + HIR111 2xmax35W

**DESIGN BY :**

Ernesto Gismondi

MATERIALS :

Extruded Aluminium

DESCRIPTION :

A range of multisource luminaires combining diffused lighting via T16 and T16-R fluorescent lamps and accent lighting via 1, 2, 3 or 4 adjustable spotlights using 12V halogen and metal-halide lamps. 3 options available: recessed, ceiling, or pendant with direct lighting. Extruded aluminium body with grey paint finish. Polycarbonate diffuser. Die-cast aluminium spotlights in steel boxes with a black paint finish. Each spot can be directed individually: tilt angle ranging from -10° to +70°, rotation of up to 355°. Integral electronic control gear. Integral electronic transformer for the halogen accent lighting, dimmable by trailing edge external dimmers. 2 separate switch circuits for the independent control of the diffused and accent lighting functions. Complies with standard EN60598-1 and other specific standards.

Light emission

Direct Diffused And Accent Lighting



TECHNICAL DATA SHEET

Features

Product name:	Andromeda Ceiling 300x600 - T16 2x24W + HIR111 2xmax35W
Article Code:	M115950
Colour:	Grey
Material:	Extruded Aluminium
Series:	Architectural
Environment:	Indoor
Area contract:	

Dimensions**OPTICS**

Emission: Direct Diffused And Accent Lighting

DIMENSIONS

Length:	(cm) 61.2
Width:	(cm) 31.2
Height:	(cm) 14.5
Inclination:	-10/+70
Rotation:	355
Cutout shape:	
Weight:	6.8
Glow Wire Test:	850 °

LAMPS NOT INCLUDED

Category:	HQI
Number:	2
Lbs:	HIR111
Watt:	35
Socket:	GX8.5
Type:	MRS/UB-35
Colour Rendering:	80-85
Colour temperature (K):	3000

Category:	FLUO
Number:	2
Lbs:	T16
Watt:	24
Socket:	G5
Type:	FDH-24
Luminous Flux (lm):	1750
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

LAMP**ELECTRICAL**

Starter:	Electronic
Transformer availability:	Integrated
Voltage:	220V-240V