PRODUCT DATA SHEET

Andromeda Ceiling 300x600 - T16 3x24W + QR-CBC 4xmax50W



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Extruded Aluminium

DESCRIPTION:

A range of multisource luminaires combining diffused lighting via T16 and T16-R fluorescent lamps and accent lighting via 1, 2, 3 or 4 adjustable spotlights using 12V halogen and metal-halide lamps. 3 options available: recessed, ceiling, or pendant with direct lighting. Extruded aluminium body with grey paint finish. Polycarbonate diffuser. Die-cast aluminium spotlights in steel boxes with a black paint finish. Each spot can be directed individually: tilt angle ranging from -10° to +70°, rotation of up to 355°. Integral electronic control gear. Integral electronic transformer for the halogen accent lighting, dimmable by trailing edge external dimmers. 2 separate switch circuits for the independent control of the diffused and accent lighting functions. Complies with standard EN60598-1 and other specific standards.

Dimmable by trailing edge external dimmer.

Light emission

Direct Diffused And Accent Lighting

IP20 🚯 🕅

TECHNICAL DATA SHEET

Features

Product name:

Article Code: Colour: Material: Series: Environment: Area contract: Andromeda Ceiling 300x600 - T16 3x24W + QR-CBC 4xmax50W M116340 Grey Extruded Aluminium Architectural Indoor

OPTICS

Emission:

Direct Diffused And Accent Lighting


DIMENSIONS

Length: (cm) 61.2 Width: (cm) 61.2 Height: (cm) 14.5 Inclination: -10/+70 Rotation: 355 Cutout shape: Weight: Weight: 12 Glow Wire Test: 850 °

LAMPS NOT INCLUDED

Category:	FLUO
Number:	3
Lbs:	T16
Watt:	24
Socket:	G5
Type:	FDH-24
Luminous Flux (Im):	1750
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000
Category:	HALO
Number:	4
Lbs:	QR-CBC51
Watt:	50
Socket:	GU5.3
Type:	HRGS/UB
Colour Rendering:	100
Colour temperature (K):	3000

Dimensions



LAMP

IP20 🚯 🕅

ELECTRICAL

Starter:	
Trasformer	availability:
Voltage:	

Electronic Integrated 220V-240V

Artemide