

# PRODUCT DATA SHEET

# Andromeda Suspension 300x600 Direct Emission - T16 2x24W + QR111 2xmax50W



### **DESIGN BY:**

Ernesto Gismondi

### **MATERIALS:**

Extruded Aluminium

### **DESCRIPTION:**

A range of multisource luminaires combining diffused lighting via T16 and T16-R fluorescent lamps and accent lighting via 1, 2, 3 or 4 adjustable spotlights using 12V halogen and metal-halide lamps. 3 options available: recessed, ceiling, or pendant with direct lighting. Extruded aluminium body with grey paint finish. Polycarbonate diffuser. Die-cast aluminium spotlights in steel boxes with a black paint finish. Each spot can be directed individually: tilt angle ranging from -10° to +70°, rotation of up to 355°. Integral electronic control gear. Integral electronic transformer for the halogen accent lighting, dimmable by trailing edge external dimmers. 2 separate switch circuits for the independent control of the diffused and accent lighting functions. Complies with standard EN60598-1 and other specific standards.

Dimmable by trailing edge external dimmer.

Maximum suspension 1300

### Light emission

Direct Diffused And Accent Lighting



### **TECHNICAL DATA SHEET**

Product name: Andromeda Suspension 300x600

Direct Emission - T16 2x24W +

QR111 2xmax50W

Article Code: M116620

Colour: Grey

Material: Extruded Aluminium
Series: Architectural
Fryironment: Indoor

Area contract:

### **OPTICS**

**Features** 

Emission: Direct Diffused And Accent Lighting

## **DIMENSIONS**

 Length:
 (cm) 61.2

 Width:
 (cm) 31.2

 Height:
 (cm) 14.5

 Inclination:
 -10/+70

 Rotation:
 355

 Cutout shape:

Weight: 8.9 Glow Wire Test: 850 °

### LAMPS NOT INCLUDED

Category: FLUO Number: Lbs: T16 Watt: 24 Socket: G5 FDH-24 Type: Luminous Flux (Im): 1750 Colour Rendering: 85 Colour temperature (K): 3000 Duration (h): 20000

 Category:
 HALO

 Number:
 1

 Lbs:
 QR111


 Watt:
 50

 Socket:
 G53

 Type:
 HMGS/UB

 Colour Rendering:
 100

### **Dimensions**



### LAMP



## **ELECTRICAL**

Starter: Electronic Trasformer availability: Integrated Voltage: 220V-240V



Colour temperature (K):

3000