

## PRODUCT DATA SHEET

### Andromeda Suspension 300x900 Direct Emission - T16 2x21W + QR111 3xmax50W



#### DESIGN BY :

Ernesto Gismondi

#### MATERIALS :

Extruded Aluminium

#### DESCRIPTION :

A range of multisource luminaires combining diffused lighting via T16 and T16-R fluorescent lamps and accent lighting via 1, 2, 3 or 4 adjustable spotlights using 12V halogen and metal-halide lamps. 3 options available: recessed, ceiling, or pendant with direct lighting. Extruded aluminium body with grey paint finish. Polycarbonate diffuser. Die-cast aluminium spotlights in steel boxes with a black paint finish. Each spot can be directed individually: tilt angle ranging from -10° to +70°, rotation of up to 355°. Integral electronic control gear. Integral electronic transformer for the halogen accent lighting, dimmable by trailing edge external dimmers. 2 separate switch circuits for the independent control of the diffused and accent lighting functions. Complies with standard EN60598-1 and other specific standards.

Dimmable by trailing edge external dimmer.  
Maximum suspension 1300

#### Light emission

Direct Diffused And Accent Lighting



### TECHNICAL DATA SHEET

#### Features

Product name:	Andromeda Suspension 300x900 Direct Emission - T16 2x21W + QR111 3xmax50W
Article Code:	M116720
Colour:	Grey
Material:	Extruded Aluminium
Series:	Architectural
Environment:	Indoor
Area contract:	

#### OPTICS

Emission:	Direct Diffused And Accent Lighting
-----------	-------------------------------------

#### DIMENSIONS


Length:	(cm) 91.2
Width:	(cm) 31.2
Height:	(cm) 14.5
Inclination:	-10/+70
Rotation:	355
Cutout shape:	
Weight:	12
Glow Wire Test:	850 °

#### LAMPS NOT INCLUDED

Category:	HALO
Number:	3
Lbs:	QR111
Watt:	50
Socket:	G53
Type:	HMGS/UB
Colour Rendering:	100
Colour temperature (K):	3000

Category:	FLUO
Number:	2
Lbs:	T16
Watt:	21
Socket:	G5
Type:	FDH-21
Luminous Flux (lm):	1900
Colour Rendering:	85
Colour temperature (K):	3000

#### Dimensions



#### LAMP



#### ELECTRICAL

Starter:	Electronic
Transformer availability:	Integrated
Voltage:	220V-240V

