

PRODUCT DATA SHEET

Andromeda Suspension 300x1200 Direct Emission - T16 2x28W + QR111 4xmax50W



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Extruded Aluminium

DESCRIPTION :

A range of multisource luminaires combining diffused lighting via T16 and T16-R fluorescent lamps and accent lighting via 1, 2, 3 or 4 adjustable spotlights using 12V halogen and metal-halide lamps. 3 options available: recessed, ceiling, or pendant with direct lighting. Extruded aluminium body with grey paint finish. Polycarbonate diffuser. Die-cast aluminium spotlights in steel boxes with a black paint finish. Each spot can be directed individually: tilt angle ranging from -10° to +70°, rotation of up to 355°. Integral electronic control gear. Integral electronic transformer for the halogen accent lighting, dimmable by trailing edge external dimmers. 2 separate switch circuits for the independent control of the diffused and accent lighting functions. Complies with standard EN60598-1 and other specific standards.

Dimmable by trailing edge external dimmer.
Maximum suspension 1300

Light emission

Direct Diffused And Accent Lighting



TECHNICAL DATA SHEET

Features

| | |
|----------------|--|
| Product name: | Andromeda Suspension 300x1200 Direct Emission - T16 2x28W + QR111 4xmax50W |
| Article Code: | M116820 |
| Colour: | Grey |
| Material: | Extruded Aluminium |
| Series: | Architectural |
| Environment: | Indoor |
| Area contract: | |

OPTICS

| | |
|-----------|-------------------------------------|
| Emission: | Direct Diffused And Accent Lighting |
|-----------|-------------------------------------|

DIMENSIONS


| | |
|-----------------|-----------|
| Length: | (cm) 121 |
| Width: | (cm) 31.2 |
| Height: | (cm) 14.5 |
| Inclination: | -10/+70 |
| Rotation: | 355 |
| Cutout shape: | |
| Weight: | 15 |
| Glow Wire Test: | 850 ° |

LAMPS NOT INCLUDED

| | |
|-------------------------|---------|
| Category: | HALO |
| Number: | 4 |
| Lbs: | QR111 |
| Watt: | 50 |
| Socket: | G53 |
| Type: | HMGS/UB |
| Colour Rendering: | 100 |
| Colour temperature (K): | 3000 |

| | |
|-------------------------|--------|
| Category: | FLUO |
| Number: | 2 |
| Lbs: | T16 |
| Watt: | 28 |
| Socket: | G5 |
| Type: | FDH-28 |
| Luminous Flux (lm): | 2600 |
| Colour Rendering: | 85 |
| Colour temperature (K): | 3000 |

Dimensions



LAMP



ELECTRICAL

| | |
|---------------------------|------------|
| Starter: | Electronic |
| Transformer availability: | Integrated |
| Voltage: | 220V-240V |

Duration (h):

20000