Artemide

PRODUCT DATA SHEET

Andromeda Suspension 300x1200 Direct Emission - T16 2x28W + HIR111 4xmax35W



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Extruded Aluminium

DESCRIPTION:

A range of multisource luminaires combining diffused lighting via T16 and T16-R fluorescent lamps and accent lighting via 1, 2, 3 or 4 adjustable spotlights using 12V halogen and metal-halide lamps. 3 options available: recessed, ceiling, or pendant with direct lighting. Extruded aluminium body with grey paint finish. Polycarbonate diffuser. Die-cast aluminium spotlights in steel boxes with a black paint finish. Each spot can be directed individually: tilt angle ranging from -10° to +70°, rotation of up to 355°. Integral electronic control gear. Integral electronic transformer for the halogen accent lighting, dimmable by trailing edge external dimmers. 2 separate switch circuits for the independent control of the diffused and accent lighting functions. Complies with standard EN60598-1 and other specific standards.

M116850 Maximum suspension 1300

Light emission

Direct Diffused And Accent Lighting

IP20 🛈 🕅

TECHNICAL DATA SHEET

Features

Product name:

Article Code: Colour: Material: Series: Environment: Area contract: Andromeda Suspension 300x1200 Direct Emission - T16 2x28W + HIR111 4xmax35W M116850 Grey Extruded Aluminium Architectural Indoor

Dimensions



OPTICS

Emission:

DIMENSIONS

Length:	(cm) 121
Width:	(cm) 31.2
Height:	(cm) 14.5
Inclination:	-10/+70
Rotation:	355
Cutout shape:	
Weight:	15
Glow Wire Test:	850 °

LAMPS NOT INCLUDED

Category:	HQI
Number:	4
Lbs:	HIR111
Watt:	35
Socket:	GX8.5
Туре:	MRS/UB-35
Colour Rendering:	80-85
Colour temperature (K):	3000
Category:	FLUO
Number:	2
Lbs:	T16
Watt:	28
Socket:	G5
Туре:	FDH-28
Luminous Flux (Im):	2600
Colour Rendering:	85
Colour temperature (K):	3000

Direct Diffused And Accent Lighting

LAMP IP20 🛈 🕅

ELECTRICAL

Starter:	
Trasformer	availability
Voltage:	

Electronic Integrated 220V-240V



Duration (h):

20000