

PRODUCT DATA SHEET

Andromeda Suspension 600x600 Direct Emission - T16 3x24W + HIR111 4xmax50W

**DESIGN BY :**

Ernesto Gismondi

MATERIALS :

Extruded Aluminium

DESCRIPTION :

A range of multisource luminaires combining diffused lighting via T16 and T16-R fluorescent lamps and accent lighting via 1, 2, 3 or 4 adjustable spotlights using 12V halogen and metal-halide lamps. 3 options available: recessed, ceiling, or pendant with direct lighting. Extruded aluminium body with grey paint finish. Polycarbonate diffuser. Die-cast aluminium spotlights in steel boxes with a black paint finish. Each spot can be directed individually: tilt angle ranging from -10° to +70°, rotation of up to 355°. Integral electronic control gear. Integral electronic transformer for the halogen accent lighting, dimmable by trailing edge external dimmers. 2 separate switch circuits for the independent control of the diffused and accent lighting functions. Complies with standard EN60598-1 and other specific standards.


Dimmable by trailing edge external dimmer.
Maximum suspension 1300

Light emission

Direct Diffused And Accent Lighting

IP20  **TECHNICAL DATA SHEET****Features**

Product name: Andromeda Suspension 600x600
Direct Emission - T16 3x24W +
HIR111 4xmax50W
Article Code: M117040
Colour: Grey
Material: Extruded Aluminium
Series: Architectural
Environment: Indoor
Area contract:

Dimensions**OPTICS**

Emission: Direct Diffused And Accent Lighting

DIMENSIONS

Length: (cm) 61.2
Width: (cm) 61.2
Height: (cm) 14.5
Inclination: -10/+70
Rotation: 355
Cutout shape:
Weight: 15
Glow Wire Test: 850 °

LAMPS NOT INCLUDED

Category: FLUO
Number: 3
Lbs: T16
Watt: 24
Socket: G5
Type: FDH-24
Luminous Flux (lm): 1750
Colour Rendering: 85
Colour temperature (K): 3000
Duration (h): 20000

Category: HALO
Number: 4
Lbs: QR-CBC51
Watt: 50
Socket: GU5.3

LAMPIP20  **ELECTRICAL**

Starter: Electronic
Trasformer availability: Integrated
Voltage: 220V-240V

Artemide

Type: HRGS/UB
Colour Rendering: 100
Colour temperature (K): 3000