

# PRODUCT DATA SHEET

## Lost Duo 1214 mm - T16 2x54W + emergency



#### **DESIGN BY:**

Ernesto Gismondi

#### **MATERIALS:**

Aluminium

#### DESCRIPTION:

Single pendant with direct-indirect lighting using 54W and 80W T16 fluorescent light source. 2 versions: lost (1xT16) and lost duo (2xT16). Dark light optics with lateral aluminium reflectors. Aluminium central profile ( lost duo). End caps in translucent injection mo polycarbonate. Light output ratio: 66%. Light distribution: 55% indirect and 45% direct. Electronic control gear, with or without dirmming (DALI-SWITCHDIM). Luminaire comes complete with quick-adjustment steel cables, ceiling surface place and power cable. Complies with standard EN60598-1 and other specific standards.

LOST DUC

For use with 2x54W or 2x80W T16. Interactive-DALI system, combining a movement detector and a daylight sensor for auto-regulation in relation to people presence and variations in daylight. Emergency lighting.

### Light emission

Indirect/direct Dark Light



### **TECHNICAL DATA SHEET**

#### **Features**

Product name: Lost Duo 1214 mm - T16 2x54W +

emergency
Article Code: M148897
Colour: N/s
Material: Aluminium

Series: Design, Architectural

Environment: Indoor

Area contract:

#### **OPTICS**

Emission: Indirect/direct Dark Light

### **DIMENSIONS**

 Length:
 (cm) 121

 Width:
 (cm) 13.2

 Height:
 (cm) 3.7

Cutout shape:

Weight: 2.5 Glow Wire Test: 850 °

#### LAMPS NOT INCLUDED

Category: FLUO Number: Lbs: T16 54 Watt: G5 Socket: FDH-54 Type: Luminous Flux (Im): 4450 Colour Rendering: 85 Colour temperature (K): Duration (h): 20000

## **Dimensions**



## LAMP



## **ELECTRICAL**

Starter: Electronic Integrated

Emergency availability: Integrated Emergency duration: 1 hour Voltage: 220V-240V