

PRODUCT DATA SHEET

Vulcania Recessed 308 - HIT-CE 150W

**DESIGN BY :**

Alessandro Pedretti

MATERIALS :

Abs/pc,aluminium

DESCRIPTION :

A range of fixed and directional recessed downlights using 12V halogen, metal-halide and fluorescent lamps. Aluminium or injection moulded plastic body. Decorative ring in ABS/PC, fixed by a simple quarter turn rotation. 3 diameter options: ø221mm, ø308mm and ø375mm. Tilt angle of up to 32°. Lamps can be maintained without the need for tools. Remote control gear. HIT version includes protective glass. Fluorescent version comes with an anti-dazzle cross-blade and integral electronic ballast. Complies with standard EN60598-1 and other specific standards.

1 x HIT-CE (G12) max150W 2x20°

Light emission

Direct Dark Light

IP20   

TECHNICAL DATA SHEET

Features

Product name:	Vulcania Recessed 308 - HIT-CE 150W
Article Code:	M106420
Colour:	White
Material:	Abs/pc,aluminium
Series:	Architectural
Environment:	Indoor
Area contract:	

OPTICS


Emission: Direct Dark Light

DIMENSIONS

Height:	(cm) 4.2
Cutout width:	(cm) 30.8
Cutout diameter:	(cm) 18.6
Recessed depth:	(cm) 32
Inclination:	32
Cutout shape:	Rounded
Weight:	1.5
Glow Wire Test:	960 °

LAMPS NOT INCLUDED

Category:	HQI
Number:	1
Lbs:	HIT-CE
Watt:	150
Socket:	G12
Type:	MT/UB-150
Luminous Flux (lm):	14000
Colour Rendering:	80-85
Colour temperature (K):	3000
Duration (h):	10000

Dimensions**LAMP**IP20   **ELECTRICAL**Transformer availability: Remote
Voltage: 220V-240V

ACCESSORIES



Electronic ballast 230-240V. Class I. For HIT 1x35W. 155x83x32mm. M070322



Electronic ballast 230-240V. Class I. For HIT 1x70W. 150x80x35mm. M070522



Electronic ballast 230-240V. Class I. For HIT 1x150W. 150x90x40mm. M070622



UV filter for HIT version M080085