

## PRODUCT DATA SHEET

### Vulcania Recessed 375 - TC-DEL 2x26W + emergency



**DESIGN BY :**

Alessandro Pedretti

**MATERIALS :**

Abs/pc,aluminium

**DESCRIPTION :**

A range of fixed and directional recessed downlights using 12V halogen, metal-halide and fluorescent lamps. Aluminium or injection moulded plastic body. Decorative ring in ABS/PC, fixed by a simple quarter turn rotation. 3 diameter options: ø221mm, ø308mm and ø375mm. Tilt angle of up to 32°. Lamps can be maintained without the need for tools. Remote control gear. HIT version includes protective glass. Fluorescent version comes with an anti-dazzle cross-blade and integral electronic ballast. Complies with standard EN60598-1 and other specific standards.

2 x TC-DEL (G24q-3) 26W + Emergency 1h

**Light emission**



Direct Dark Light




### TECHNICAL DATA SHEET

**Features**

|                |   |
|----------------|---|
| Product name:  | Vulcania Recessed 375 - TC-DEL<br>2x26W + emergency |
| Article Code:  | M106527   |
| Colour:        | White   |
| Material:      | Abs/pc,aluminium                                    |
| Series:        | Architectural                                       |
| Environment:   | Indoor  |
| Area contract: |   |

**Dimensions**



**OPTICS**

|           |                   |
|-----------|-------------------|
| Emission: | Direct Dark Light |
|-----------|-------------------|

**DIMENSIONS**

|                  |           |
|------------------|-----------|
| Height:          | (cm) 5.5  |
| Cutout width:    | (cm) 37.5 |
| Cutout diameter: | (cm) 22   |
| Recessed depth:  | (cm) 11.5 |
| Cutout shape:    | Rounded   |
| Weight:          | 2.7       |
| Glow Wire Test:  | 850 °     |

**LAMPS NOT INCLUDED**

|                         |        |
|-------------------------|--------|
| Category:               | FLUO   |
| Number:                 | 2      |
| Lbs:                    | Tc-d   |
| Watt:                   | 26     |
| Socket:                 | G24d-3 |
| Type:                   | Fsq    |
| Colour Rendering:       | 1b     |
| Colour temperature (K): | 3000   |
| Duration (h):           | 12000  |

**LAMP**



**ELECTRICAL**

|                         |                       |
|-------------------------|-----------------------|
| Starter:                | Electronic Integrated |
| Emergency availability: | Integrated            |
| Emergency duration:     | 1 hour                |
| Voltage:                | 220V-240V             |

## ACCESSORIES

---



Electronic transformer  
230-240V/12V. Class II.  
Dimmable by trailing or  
leading edge external  
dimmers. 10-60W.  
123x32x23mm. M070211



Electronic transformer  
230-240V/12V. Class II.  
Dimmable by trailing or  
leading edge external  
dimmers. 35-105W.  
102x51x30mm. M070412