Artemide

PRODUCT DATA SHEET

Oto 130 Halo - QR111 - Grey/Black



DESIGN BY:

Foster & Partners

MATERIALS:

Die-cast Aluminium, extruded Aluminium

DESCRIPTION:

A range of directional spotlights using 12V or 230/240V halogen and metal halide lamps. With three-phase track adapter. Aluminium body comprised of an optical and power supply unit. Optical unit available in 2 diameter options depending on the light source: ø80mm and ø130mm. Aluminium optics with various beam spreads. Tilt angle of up to 90°, rotation of up to 355°. Electronic control gear.

Complies with standard EN60598-1 and other specific standards.

Integral electronic transformer 35-100W, 230-240V/12V. Dimmable by trailing edge external dimmers.

Light emission

Accent Lighting



TECHNICAL DATA SHEET

Features
Product name: Oto 130 Halo - QR111 - Grey/Black

Article Code: L231200

Colour: Grey/Black

Material: Die-cast Aluminium, extruded Aluminium

Series: Architectural Indoor

Area contract:

OPTICS

Emission: Accent Lighting

DIMENSIONS

 Length:
 (cm) 24.4

 Height:
 (cm) 22.5

 Cutout width:
 (cm) 13

 Inclination:
 90

 Rotation:
 355


Cutout shape:

Weight: 1.6

LAMPS NOT INCLUDED

Category: HALO Number: Lbs: QR111 Watt: 100 Socket: G53 HMGS/UB Type: Colour Rendering: 100 Colour temperature (K): 3000 Duration (h): 3000

Dimensions



LAMP





ELECTRICAL

Starter: Electronic Integrated
Trasformer availability: Integrated
Transformer voltage: 35-100W

Emergency availability: Dimmable by trailing edge external

dimmers

Voltage: 220V-240V/12V



ACCESSORIES



OTO 130 - Accessoryholder + light-shade grill L238000



OTO 130 - Accessoryholder + adjustable dowser L238100



OTO 130 - Accessoryholder + wall washer screen L238200



OTO 130 - Accessoryholder + UV filter L238400



OTO 130 - Accessoryholder + Infrared filter L238500