

PRODUCT DATA SHEET

Oto 130 Halo - QR111 - White



DESIGN BY :

Foster & Partners

MATERIALS :

Die-cast Aluminium, extruded Aluminium

DESCRIPTION :

A range of directional spotlights using 12V or 230/240V halogen and metal halide lamps. With three-phase track adapter. Aluminium body comprised of an optical and power supply unit. Optical unit available in 2 diameter options depending on the light source: ø80mm and ø130mm. Aluminium optics with various beam spreads. Tilt angle of up to 90°, rotation of up to 355°. Electronic control gear. Safety glass with HIT version. Wide range of accessories. Complies with standard EN60598-1 and other specific standards.

Integral electronic transformer 35-100W, 230-240V/12V.
Dimmable by trailing edge external dimmers.

Light emission

Accent Lighting



TECHNICAL DATA SHEET

Features

Product name:	Oto 130 Halo - QR111 - White
Article Code:	L231220
Colour:	White
Material:	Die-cast Aluminium, extruded Aluminium
Series:	Architectural
Environment:	Indoor
Area contract:	

OPTICS

Emission:	Accent Lighting
-----------	-----------------


DIMENSIONS

Length:	(cm) 24.4
Height:	(cm) 22.5
Cutout width:	(cm) 13
Inclination:	90
Rotation:	355
Cutout shape:	
Weight:	1.6

LAMPS NOT INCLUDED

Category:	HALO
Number:	1
Lbs:	QR111
Watt:	100
Socket:	G53
Type:	HMGS/UB
Colour Rendering:	100
Colour temperature (K):	3000
Duration (h):	3000

Dimensions



LAMP



ELECTRICAL

Starter:	Electronic Integrated
Transformer availability:	Integrated
Transformer voltage:	35-100W
Emergency availability:	Dimmable by trailing edge external dimmers
Voltage:	220V-240V/12V

ACCESSORIES



OTO 130 - Accessory-holder + light-shade grill L238000



OTO 130 - Accessory-holder + adjustable dowser L238100



OTO 130 - Accessory-holder + wall washer screen L238200



OTO 130 - Accessory-holder + UV filter L238400



OTO 130 - Accessory-holder + Infrared filter L238500