

PRODUCT DATA SHEET

Rivoli Recessed T16 - 28W dimmable DALI



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Anodized Aluminium

DESCRIPTION :

A range of outdoor luminaires for T16 fluorescent lamps for lighting facades or vertical surfaces. 2 options: recessed into the ground or surface mounted. Electronic control gear. Connection and branch box to be ordered separately. Complies with standard EN60598-1 and other specific standards.

Rivoli recessed

Extruded aluminium body. End caps made from die-cast aluminium. Diffuser in 8mm thick screen-printed tempered glass. Recessing box to be ordered separately. Ip67. Luminaire includes lamp and power supply cable.

Max load 20000 N
T max glass 53°

Light emission



Direct

IP67



TECHNICAL DATA SHEET

Features

Product name:	Rivoli Recessed T16 - 28W dimmable DALI
Article Code:	M129100
Colour:	Aluminium
Material:	Anodized Aluminium
Series:	Architectural, Outdoor
Environment:	Outdoor

OPTICS

Emission:	Direct
-----------	--------

DIMENSIONS

Length:	(cm) 126
Width:	(cm) 11.4
Recessed depth:	(cm) 12.7
Cutout shape:	
Weight:	5.7
Impact Resistance:	IK10

LAMPS NOT INCLUDED

Category:	FLUO
Number:	1
Lbs:	T16
Watt:	28
Socket:	G5
Type:	FDH-28
Luminous Flux (lm):	2600
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

Dimensions



LAMP

IP67




ELECTRICAL

Starter:	Electronic dimmable DALI Integrated
Voltage:	220V-240V

ACCESSORIES



RIVOLI - Connection and
branch box (IP67).
M073130



RIVOLI - Recessing box.
For T16 28/54W.
1264x118mm M129400