

## PRODUCT DATA SHEET

### Rivoli Recessed T16 - 54W dimmable DALI



#### DESIGN BY :

Ernesto Gismondi

#### MATERIALS :

Anodized Aluminium

#### DESCRIPTION :

A range of outdoor luminaires for T16 fluorescent lamps for lighting facades or vertical surfaces. 2 options: recessed into the ground or surface mounted. Electronic control gear. Connection and branch box to be ordered separately. Complies with standard EN60598-1 and other specific standards.

#### Rivoli recessed

Extruded aluminium body. End caps made from die-cast aluminium. Diffuser in 8mm thick screen-printed tempered glass. Recessing box to be ordered separately. Ip67. Luminaire includes lamp and power supply cable.

Max load 20000 N  
T max glass 53°

#### Light emission



Direct

IP67



#### TECHNICAL DATA SHEET

#### Features

Product name:	Rivoli Recessed T16 - 54W dimmable DALI
Article Code:	M129200
Colour:	Aluminium
Material:	Anodized Aluminium
Series:	Architectural, Outdoor
Environment:	Outdoor

#### OPTICS

Emission:	Direct
-----------	--------

#### DIMENSIONS

Length:	(cm) 126
Width:	(cm) 11.4
Recessed depth:	(cm) 12.7
Cutout shape:	
Weight:	5.7
Impact Resistance:	IK10

#### LAMPS NOT INCLUDED

Category:	FLUO
Number:	1
Lbs:	T16
Watt:	54
Socket:	G5
Type:	FDH-54
Luminous Flux (lm):	4450
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

#### Dimensions



#### LAMP

IP67



#### ELECTRICAL


Starter:	Electronic dimmable DALI Integrated
Voltage:	220V-240V

## ACCESSORIES

---



RIVOLI - Connection and  
branch box (IP67).  
M073130



RIVOLI - Recessing box.  
For T16 28/54W.  
1264x118mm M129400