PRODUCT DATA SHEET

Rivoli Cornice T16 - 35W



DESIGN BY :

Ernesto Gismondi

MATERIALS :

Anodized Aluminium

DESCRIPTION:

A range of outdoor luminaires for T16 fluorescent lamps for lighting facades or vertical surfaces. 2 options: recessed into the ground or surface mounted. Electronic control gear. Connection and branch box to be ordered separately. Complies with standard ENn60598-1 and other specific standards.

Rivoli cornice

Extruded aluminium body. End caps made from die-cast aluminium. Aluminium optic unit. Diffuser in 5mm thick screenprinted tempered glass. Suitable for wall mounting with lighting directed upwards or downwards, and for ceiling mounting. Multi-position fixing mechanism to be ordered separately. Luminaire includes lamp and power supply cable.

Light emission

Direct

IP65 🛈 🐼

TECHNICAL DATA SHEET

Features

Product name: Article Code: Colour: Material: Series: Environment:

OPTICS

Emission:

DIMENSIONS

Length:	(cm) 155
Width:	(cm) 7.6
Height:	(cm) 8.1
Cutout shape:	
Weight:	5.8
Impact Resistance:	IK09

LAMPS NOT INCLUDED

Category:	FLUO
Number:	1
Lbs:	T16
Watt:	35
Socket:	G5
Туре:	FDH-35
Luminous Flux (Im):	3300
Colour Rendering:	85
Colour temperature (K):	3000
Duration (h):	20000

Rivoli Cornice T16 - 35W	
M103200	
N/s	
Anodized Aluminium	
Architectural, Outdoor	
Outdoor	

Direct



LAMP

IP65 🛈 🌃

Dimensions

ELECTRICAL

Starter: Voltage: Electronic Integrated 220V-240V



ACCESSORIES







RIVOLI - Wall fixing bracket (1 piece). 2 pieces required per luminaire. M126600