

## PRODUCT DATA SHEET

### Stick 210 - HIT G8,5 2x20° - Moka



#### DESIGN BY :

Wilmotte & Industries

#### MATERIALS :

Steel

#### DESCRIPTION :

A range of recessed adjustable downlights using 12V halogen, metal-halide and 230-240V LED lamps. Square frame made from steel, available in three colour options. Optical unit made from aluminium with a chrome finish. 2 size options depending on the light source. Super pure aluminium optics with HIT version, with choice of 3 beam spreads: spot, medium and flood, tilt angle of up to 40° with a chrome steel rod. Rotation of up to 360°, lamps can be maintained without the need for tools. HIT version includes protective glass. Remote control gear. Complies with standard EN60598-1 and other specific standards.

1 x HIT-TC-CE (G8,5) max70W 2x20°

#### Light emission



Direct



### TECHNICAL DATA SHEET

#### Features

Product name:	Stick 210 - HIT G8,5 2x20° - Moka
Article Code:	M022415
Colour:	Moka
Material:	Steel
Series:	Architectural
Environment:	Indoor
Area contract:	

#### OPTICS

Emission:	Direct
-----------	--------


#### DIMENSIONS

Length:	(cm) 21
Width:	(cm) 21
Height:	(cm) 19
Cutout length:	(cm) 19.8
Cutout Width:	(cm) 19.8
Recessed depth:	(cm) 19
Inclination:	40
Rotation:	360
Cutout shape:	Squared
Weight:	2.6
Glow Wire Test:	960 °

#### LAMPS NOT INCLUDED

Category:	HQI
Number:	1
Lbs:	HIT-TC-CE
Watt:	70
Socket:	G8.5
Type:	MT/UB-70
Luminous Flux (lm):	6600
Colour Rendering:	80-85
Colour temperature (K):	3000

#### Dimensions



#### LAMP



#### ELECTRICAL

Starter:	Electronic Remote
Voltage:	230V-240V

## ACCESSORIES

---



Electronic ballast 230-240V. Class I. For HIT 1x35W. 155x83x32mm.  
M070322



Electronic ballast 230-240V. Class I. For HIT 1x70W. 150x80x35mm.  
M070522