PRODUCT DATA SHEET

Picto 125 LED Ceiling - 3000K dimmable - White



DESIGN BY :

Artemide

MATERIALS :

Aluminium

DESCRIPTION :

Directional spotlight using monochromatic Led with warm white tone. Comes with surface plate for ceiling mounting. Body made from aluminium and injection moulded high-quality polyamide. Tilt angle ranging from -90° to 90°, rotation of up to 355°. Precise inclination by means of a graduation specially designed, with a locking mechanism. Electronic power supply. Wide range of accessories. Not suitable for wall installation. Complies with standard EN60598-1 and other specific standards.

Optic FL (2x15° < angle < 2x20°)

Light emission



TECHNICAL DATA SHEET

Features

Product name:

Colour: Material: Series: Environment: Area contract:

OPTICS Emission:

Width:

Height:

Weight:

Category:

Number:

Class:

Typology:

Watt:

DIMENSIONS

Cutout width:

Cutout shape:

Glow Wire Test:

Wattage (Single):

Luminous Flux (Im):

Color temperature (K):

LAMPS INCLUDED

Inclination: Rotation: Picto 125 LED Ceiling - 3000K dimmable - White White Aluminium Architectural Indoor Retail, Museum & Exihibitions, , Private Residence

Accent Lighting

(cm) 12.7

(cm) 17.2

(cm) 12.7 -90/+90

355

2.3

850 °

I FD

33

33

1174


1 x 1

3000

1

А

Dimensions



LAMP

IP20 🛈 🕅

+0

ELECTRICAL

Trasformer availability: Voltage: Dimmable DALI 220V-240V

Artemide

ACCESSORIES



PICTO 125 - Accessoryholder + Chromatic filter 'Warmtone". Black M083637



PICTO 125 - Accessoryholder + Adjustable dowser (black). black M082937





PICTO 125 - Accessoryholder + Lens for elliptical light distribution. Black M083437

pry- PICTO 125 - Accessoryptical holder + Louvre (black). ack black M083337



PICTO 125 - Accessoryholder + wall washer screen (black). black M083137