

## PRODUCT DATA SHEET

### Picto 70 Halo Vertical Ceiling - White/Anthracite Grey



**DESIGN BY :**

Artemide

**MATERIALS :**

Aluminium and polyamide

**DESCRIPTION :**

Series of directional spotlights using high yield hite LED, metal-halide and 12V halogen lamps. Body made from aluminium and injection moulded high-quality polyamide. Choice of 5 colour options. Two design options: with horizontal or vertical power supply unit with small, medium and large size. Optic unit available in 3 sizes:  $\varnothing 70\text{mm}$ ,  $\varnothing 100\text{mm}$  and  $\varnothing 125\text{mm}$ . 2 versions: with three-phase track adapter, and with base plate for ceiling mounting. Super pure aluminum optics with a choice of up to four beam spreads, freely interchangeable. Tilt angle ranging from  $-90^\circ$  to  $90^\circ$ , rotation of up to  $355^\circ$ . Precise inclination by means of a graduation specially designed, with a locking mechanism. Monochromatic LED with warm white and neutral white tones. HIT version includes protection glass. Electronic control gear. Wide range of accessories. Not suitable for wall installation. Complies with standard EN60598-1 and other specific standards.

**Light emission**



Accent Lighting




### TECHNICAL DATA SHEET

**Features**

Product name:	Picto 70 Halo Vertical Ceiling - White/Anthracite Grey
Article Code:	M223021
Colour:	White/Anthracite Grey
Material:	Aluminium and polyamide
Series:	Architectural
Environment:	Indoor
Area contract:	Retail, Museum & Exhibitions, Private Residence

**Dimensions**



**OPTICS**

Emission:	Accent Lighting
-----------	-----------------


**DIMENSIONS**

Length:	(cm) 7.8
Height:	(cm) 14.2
Depth:	(cm) 4.4
Cutout width:	(cm) 7.2
Inclination:	$-90+90$
Rotation:	355
Cutout shape:	
Weight:	1.4
Glow Wire Test:	850 °

**LAMPS NOT INCLUDED**

Category:	HALO
Number:	1
Lbs:	QR-CBC51
Watt:	50
Socket:	GU5.3
Type:	HRGS/UB
Colour Rendering:	100
Colour temperature (K):	3000

**LAMP**



**ELECTRICAL**

Transformer availability:	Integrated
Transformer voltage:	20-50W
Emergency availability:	Dimmable by trailing or leading edge external dimmers.
Voltage:	220V-240V

## ACCESSORIES

---



PICTO 70 - Accessory-holder + wall washer screen (black). anthracite-grey M083027



PICTO 70 - Accessory-holder + Projection lens for gobo. Customized gobo to be ordered separately. anthracite-grey M083827



PICTO 70 - Accessory-holder + projection lens and framing device. anthracite-grey M083927



PICTO 70 - Accessory-holder + Adjustable dowser (black). anthracite-grey M082827



PICTO 70 - Accessory-holder + wall washer screen (black). anthracite-grey M083027