

PRODUCT DATA SHEET

Picto 100 Horizontal Ceiling - HIT 35W SP - Black/White



DESIGN BY :

Artemide

MATERIALS :

Aluminium and polyamide

DESCRIPTION :

Series of directional spotlights using high yield hite LED, metal-halide and 12V halogen lamps. Body made from aluminium and injection moulded high-quality polyamide. Choice of 5 colour options. Two design options: with horizontal or vertical power supply unit with small, medium and large size. Optic unit available in 3 sizes: ø70mm, ø100mm and ø125mm. 2 versions: with three-phase track adapter, and with base plate for ceiling mounting. Super pure aluminum optics with a choice of up to four beam spreads, freely interchangeable. Tilt angle ranging from -90° to 90°, rotation of up to 355°. Precise inclination by means of a graduation specially designed, with a locking mechanism. Monochromatic LED with warm white and neutral white tones. HIT version includes protection glass. Electronic control gear. Wide range of accessories. Not suitable for wall installation. Complies with standard EN60598-1 and other specific standards.

Optic SP (2x5° < angle < 2x10°)

Optic MFL (2x10° < angle < 2x15°)

Optic FL (2x15° < angle < 2x20°)

Optic WFL (2x20° < Angle < 2x30°)

Light emission



Accent Lighting




TECHNICAL DATA SHEET

Features

Product name:	Picto 100 Horizontal Ceiling - HIT 35W SP - Black/White
Article Code:	M224711SP
Colour:	Black/White
Material:	Aluminium and polyamide
Series:	Architectural
Environment:	Indoor
Area contract:	Retail, Museum & Exhibitions, Private Residence

Dimensions



OPTICS

Emission:	Accent Lighting
-----------	-----------------

DIMENSIONS

Length:	(cm) 13.2
Height:	(cm) 11.1
Depth:	(cm) 4.4
Cutout width:	(cm) 10
Inclination:	-90+90
Rotation:	355
Cutout shape:	
Weight:	1.6
Glow Wire Test:	850 °

LAMPS NOT INCLUDED

Category:	HQI
Number:	1
Lbs:	HIT-TC-CE
Watt:	35
Socket:	G8.5
Type:	MT/UB-35
Luminous Flux (lm):	3000
Colour Rendering:	80-85
Colour temperature (K):	3000
Duration (h):	9000

LAMP



ELECTRICAL

Starter:	Electronics integrated
Voltage:	220V-240V

ACCESSORIES



PICTO 100 - Accessory-holder + Louvre (black). White M081717



PICTO 100 - Accessory-holder + wall washer screen (black). white M082717



PICTO 100 - Accessory-holder + Adjustable dowser (black). white M082617



PICTO 100 HIT - UV-Filter. M080545