

# PRODUCT DATA SHEET

## Picto 100 Horizontal Ceiling - HIT 35W MFL - White/Anthracite grey



#### **DESIGN BY:**

Artemide

#### **MATERIALS:**

Aluminium and polyamide

#### **DESCRIPTION:**

Series of directional spotlights using high yield hite LED, metal-halide and 12V halogen lamps. Body made from Series of directional spotlights using high yield hite LED, metal-halide and 12V halogen lamps. Body made from aluminium and injection moulded high-quality polyamide. Choice of 5 colour options. Two design options: with horizontal or vertical power supply unit with small, medium and large size. Optic unit available in 3 sizes: #70mm, #100mm and #125mm. 2 versions: with three-phase track adapter, and with base plate for ceiling mounting. Super pure aluminum optics with a choice of up to four beam spreads, freely interchangeable. Tilt angle ranging from -90° to 90°, rotation of up to 355°, Precise inclination by means of a graduation specially designed, with a locking mechanism.

Monochromatic LED with warm white and neutral white tones. HIT version includes protection glass. Electronic control gear, Wide range of accessories. Not suitable for wall installation. Complies with standard EN60598-1 and other specific standards. standards

Optic MFL (2x10° < angle < 2x15°)

### Light emission



Accent Lighting



## **TECHNICAL DATA SHEET**

**Features** 

Product name: Picto 100 Horizontal Ceiling - HIT

35W MFL - White/Anthracite grey

Article Code: M224721MFL

Colour: White/Anthracite grey Material: Aluminium and polyamide

Series: Architectural **Environment:** Indoor

Area contract: Retail, Museum & Exihibitions,

Private Residence

**OPTICS** 

Emission: Accent Lighting

#### **DIMENSIONS**

(cm) 13.2 Length: Height: (cm) 11.1 (cm) 4.4 Depth: Cutout width: (cm) 10 -90+90 Inclination: 355 Rotation:


Cutout shape:

Weight: 1.6 Glow Wire Test:

### LAMPS NOT INCLUDED

Category: HOI Number: Lbs: HIT-TC-CE Watt: 35 G8.5 Socket: MT/UB-35 Type: Luminous Flux (Im): 3000 Colour Rendering: 80-85 Colour temperature (K): 3000 Duration (h):

### **Dimensions**



#### LAMP



## **ELECTRICAL**

Starter: Electronics integrated 220V-240V Voltage:



## **ACCESSORIES**



PICTO 100 - Accessoryholder + Louvre (black). anthracite-grey M081727



PICTO 100 - Accessoryholder + wall washer screen (black). anthracitegrey M082727



PICTO 100 - Accessoryholder + Adjustable dowser (black). anthracite-grey M082627



PICTO 100 HIT - UV-Filter. M080545