# **Artemide**

# PRODUCT DATA SHEET

# Picto 100 Horizontal Ceiling - HIT 70W WFL - Black/White



#### **DESIGN BY :**

Artemide

#### MATERIALS :

Aluminium and polyamide

#### **DESCRIPTION:**

Series of directional spotlights using high yield hite LED, metal-halide and 12V halogen lamps. Body made from aluminium and injection moulded high-quality polyamide. Choice of 5 colour options. Two design options: with horizontal or vertical power supply unit with small, medium and large size. Optic unit available in 3 sizes: a70mm, ø100mm and ø125mm. 2 versions: with three-phase track adapter, and with base plate for ceiling mounting. Super pure aluminum optics with a choice of up to four beam spreads, freely interchangeable. Tilt angle ranging from -90° to 90°, rotation of up to 355°. Precise inclination by means of a graduation specially designed, with a locking mechanism. Monochromatic LED with warm white and neutral white tones. HIT version includes protection glass. Electronic control gear. Wide range of accessories. Not suitable for wall installation. Complies with standard EN60598-1 and other specific standards.

Optic WFL (2x20° < Angle < 2x30°)

#### Light emission



Accent Lighting

IP20 🚯 🕅

**TECHNICAL DATA SHEET** 

#### Features

Product name: Article Code: Colour: Material: Picto 100 Horizontal Ceiling - HIT 70W WFL - Black/White M224811WFL Black/White Aluminium and polyamide Architectural Indoor Retail, Museum & Exihibitions, Private Residence

#### OPTICS

Series:

Environment:

Area contract:

Emission:

Accent Lighting


## DIMENSIONS

(cm) 13.2 Length: Height: (cm) 11.1 (cm) 4.4 Depth: Cutout width: (cm) 10 -90+90 Inclination: 355 Rotation: Cutout shape: Weight: 1.6 Glow Wire Test: 850 °

## LAMPS NOT INCLUDED

| Category:               | HQI       |
|-------------------------|-----------|
| Number:                 | 1         |
| Lbs:                    | HIT-TC-CE |
| Watt:                   | 70        |
| Socket:                 | G8.5      |
| Туре:                   | MT/UB-70  |
| Colour Rendering:       | 80-85     |
| Colour temperature (K): | 3000      |
| Duration (h):           | 12000     |
|                         |           |

#### Dimensions



#### LAMP

IP20 🛈 🕅

## ELECTRICAL

Starter: Voltage: Electronics integrated 220V-240V

# Artemide





PICTO 100 - Accessoryholder + Louvre (black). White M081717



PICTO 100 - Accessoryholder + wall washer screen (black). white M082717



PICTO 100 - Accessoryholder + Adjustable dowser (black). white M082617



**PICTO 100 HIT - UV-Filter.** M080545