Artemide

PRODUCT DATA SHEET

Dado 10° 3000K



DESIGN BY:

Nord Light 2009

MATERIALS:

Aluminium

DESCRIPTION:

Light fixture with high-performance

LED light sources. Wall installation. Square version.

Adjustable spot lamp on the axis perpendicular to the wall (90°) and on the axis parallel to the wall by means of spot head rotation (355°).

Composed by adjustable structure, spot unit, diffuser in transparent polycarbonate.

Spot unit in computer numerical control machined billet anticorodal aluminium.

Painted projector with 2-stage outdoor treatment:primer, outdoor paint.

Anodized finishing.

Electrical connection to the mains by means of remote ballast.

Silicone gaskets.

50 cm-long two-pole connection cable H05RN-F.

Aluminium wall fixing bracket.

Technical features of light fixtures in compliance with EN60598-1 and part 2-13.

PMMA lenses. Fixed optic.(Beams 10°)

White monochromatic LEDs available.

Colour temperatures:

Warm = 3000K

Light emission







TECHNICAL DATA SHEET

Features

Product name: Dado 10° 3000K NL734810K0 Article Code: Colour: Aluminium Material: Aluminium

Series: Nord Light, Outdoor

Hospitality Hotel, Outdoor Facade Area contract:

DIMENSIONS


Length: (cm) 20 Width: (cm) 5 Height: (cm) 5

Cutout shape:

LAMPS INCLUDED

Category: LED Watt: 5W Wattage (Single): Number: 1 x 1 Typology: Color temperature (K): 3000K Class: Current: 350 mA

Dimensions



LAMP



ELECTRICAL

Starter: Electronic ballast 350mA