# Artemide

# PRODUCT DATA SHEET

# Picto 100 Halo Horizontal Ceiling - SP - White/Anthracite grey

Picto 100 Halo Horizontal Ceiling -

Accent Lighting



### **DESIGN BY :**

Artemide

#### MATERIALS :

Aluminium and polyamide

#### **DESCRIPTION**:

Series of directional spotlights using high yield hite LED, metal-halide and 12V halogen lamps. Body made from Series of directional spotlights using high yield hite LED, metal-halide and 12V halogen lamps. Body made from aluminium and injection moulded high-quality polyamide. Choice of 5 colour options. Two design options: with horizontal or vertical power supply unit with small, medium and large size. Optic unit available in 3 sizes: #70mm, #100mm and #125mm. 2 versions: with three-phase track adapter, and with base plate for ceiling mounting. Super pure aluminum optics with a choice of up to four beam spreads, freely interchangeable. Tilt angle ranging from -90° to 90°, rotation of up to 355°. Precise inclination by means of a graduation specially designed, with a locking mechanism. Monochromatic LED with warm white and neutral white tones. HIT version includes protection glass. Electronic control gear. Wide range of accessories. Not suitable for wall installation. Complies with standard EN60598-1 and other specific standards. standards.

Optic SP (2x5° < angle < 2x10°)

Accent Lighting

#### Light emission



**TECHNICAL DATA SHEET** 

#### Features

Product name:

SP - White/Anthracite grey Article Code: M224921SP Colour: White/Anthracite grey Material: Aluminium and polyamide Series: Architectural Environment: Indoor Area contract: Retail, Museum & Exihibitions, Private Residence

#### OPTICS

Emission:


## DIMENSIONS

Length:	(cm) 13.2
Height:	(cm) 11.1
Depth:	(cm) 4.4
Cutout width:	(cm) 10
Inclination:	-90+90
Rotation:	355
Cutout shape:	
Weight:	1.6
Glow Wire Test:	850 °

## LAMPS NOT INCLUDED

Category:	HALO
Number:	1
Lbs:	Qt12-lp
Watt:	60
Socket:	Gy6.35
Туре:	N/s
Colour Rendering:	1a
Colour temperature (K):	3000
Duration (h):	4000

Dimensions



LAMP IP20 🛈 🕅

# +0-

# ELECTRICAL

Trasformer availability: Transformer voltage: Emergency availability:

Voltage:

Integrated 20-60W Dimmable by trailing or leading edge external dimmers 220V-240V

# Artemide





PICTO 100 - Accessoryholder + Louvre (black). anthracite-grey M081727



PICTO 100 - Accessoryholder + wall washer screen (black). anthracitegrey M082727



PICTO 100 - Accessoryholder + Adjustable dowser (black). anthracite-grey M082627



**PICTO 100 HIT - UV-Filter.** M080545