

## PRODUCT DATA SHEET

### Picto 100 Halo Horizontal Ceiling - FL - White/Anthracite grey



#### DESIGN BY :

Artemide

#### MATERIALS :

Aluminium and polyamide

#### DESCRIPTION :

Series of directional spotlights using high yield hite LED, metal-halide and 12V halogen lamps. Body made from aluminium and injection moulded high-quality polyamide. Choice of 5 colour options. Two design options: with horizontal or vertical power supply unit with small, medium and large size. Optic unit available in 3 sizes: ø70mm, ø100mm and ø125mm. 2 versions: with three-phase track adapter, and with base plate for ceiling mounting. Super pure aluminum optics with a choice of up to four beam spreads, freely interchangeable. Tilt angle ranging from -90° to 90°, rotation of up to 355°. Precise inclination by means of a graduation specially designed, with a locking mechanism. Monochromatic LED with warm white and neutral white tones. HIT version includes protection glass. Electronic control gear. Wide range of accessories. Not suitable for wall installation. Complies with standard EN60598-1 and other specific standards.

Optic FL (2x15° < angle < 2x20°)

#### Light emission



Accent Lighting




## TECHNICAL DATA SHEET

#### Features

Product name:	Picto 100 Halo Horizontal Ceiling - FL - White/Anthracite grey
Article Code:	M224921FL
Colour:	White/Anthracite grey
Material:	Aluminium and polyamide
Series:	Architectural
Environment:	Indoor
Area contract:	Retail, Museum & Exhibitions, Private Residence

#### Dimensions



#### OPTICS

Emission:	Accent Lighting
-----------	-----------------

#### DIMENSIONS

Length:	(cm) 13.2
Height:	(cm) 11.1
Depth:	(cm) 4.4
Cutout width:	(cm) 10
Inclination:	-90+90
Rotation:	355
Cutout shape:	
Weight:	1.6
Glow Wire Test:	850 °

#### LAMPS NOT INCLUDED

Category:	HALO
Number:	1
Lbs:	Qt12-lp
Watt:	60
Socket:	Gy6.35
Type:	N/s
Colour Rendering:	1a
Colour temperature (K):	3000
Duration (h):	4000

#### LAMP



#### ELECTRICAL

Transformer availability:	Integrated
Transformer voltage:	20-60W
Emergency availability:	Dimmable by trailing or leading edge external dimmers.
Voltage:	220V-240V

## ACCESSORIES



PICTO 100 - Accessory-holder + Louvre (black). anthracite-grey M081727



PICTO 100 - Accessory-holder + wall washer screen (black). anthracite-grey M082727



PICTO 100 - Accessory-holder + Adjustable dowser (black). anthracite-grey M082627



PICTO 100 HIT - UV-Filter. M080545